PRODUCT-DETAILS

PR222DS/PD-LSIG In=400 MODBUS T5 3p

PR222DS/PD-LSIG In=400 MODBUS T5 3p



General Information

Extended Product Type	PR222DS/PD-LSIG In=400 MODBUS T5 3p
Product ID	1SDA054714R1
EAN	8015644558284
Catalog Description	PR222DS/PD-LSIG In=400 MODBUS T5 3p
Long Description	SOLID-STATE RELEASE THREE-POLE IN AC PR222DS/PD-LSIG R 400 MODBUS T5

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK108467A6707

© 2024 ABB. All rights reserved.

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644558284
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions

Product Net Weight	1.3 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	12 mm
Package Level 1 Height	16 mm
Package Level 1 Depth / Length	19 mm
Package Level 1 Gross Weight	1.4 kg
Package Level 1 EAN	8015644558284

Additional Information

Configuration Type	Loose or configurable
Number of Poles	3
Product Main Type	Accessories for Tmax T
Product Name	Accessory
Product Type	Accessory
Rated Current (I_n)	400 A
Release	PR222DS/PD-LSIG
Release Type	Electronic
Standards	IEC
Suitable For	T5
Suitable for Product Class	SACE Tmax T

Certificates and Declarations

Data Sheet, Technical Information	1SDC210015D0201
Declaration of Conformity - CE	1SDL000165R0001
Instructions and Manuals	1SDC210015D0201

Classifications

ETIM 7	EC001023 - Shunt release (for power circuit breaker)

© 2024 ABB. All rights reserved.

ETIM 8	EC001023 - Shunt release (for power circuit breaker)
ETIM 9	EC001023 - Shunt release (for power circuit breaker)
Object Classification Code	Q
UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370418

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Accessories for Tmax T



© 2024 ABB. All rights reserved.