PRODUCT-DETAILS

E3H/VF2000PR122VFIn2000A3pFHR1000V
E3H/VF 2000 PR122VF In2000A 3p FHR 1000V



General Information

Extended Product Type	E3H/VF2000PR122VFIn2000A3pFHR1000V
Product ID	1SDA069479R1
EAN	8015644702021
Catalog Description	E3H/VF 2000 PR122VF In2000A 3p FHR 1000V
Long Description	SACE EMAX CIRCUIT-BREAKER E3H/VF 2000A 1000V AC THREE-POLE FIXED WITH TERMINALS REAR HORIZONTAL OVERCURRENT RELEASE PR122/VF-LI R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED SPEC.VERS.IEC FOR LOW FREQUENCY 1...60HZ

Circular Value

Conflict Minerals Reporting Template (CMRT)	Document availability on demand
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental

Environmental Information	9AKK10103A6076

© 2024 ABB. All rights reserved.

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering

EAN	8015644702021
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 EAN	8015644609139

Additional Information

Current Type	AC
Number of Poles	3
Power Loss	130 W
Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Current (I_n)	2000 A
Rated Voltage (U_r)	1000 V
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current (I_e)	2000 A
Rated Operational Voltage	1000 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(690 V AC) 20 kA (1000 V AC) 15 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(690 V AC) 20 kA (1000 V AC) 15 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR122 VF
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E3

© 2024 ABB. All rights reserved.

Terminal Connection Type	Fixed Circuit-Breakers Rear flat Horizontal
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC007904D0201
Declaration of Conformity - CE	1SDL000165R0015
Instructions and Manuals	1SDH000909R0001 1SDH000910R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax



© 2024 ABB. All rights reserved.