PRODUCT-DETAILS

# E6.2X/MS 6300 3p F HR

## E6.2X/MS 6300 3p F HR



### General Information

| | |
|---|---|
| Extended Product Type | E6.2X/MS 6300 3p F HR |
| Product ID | 1SDA073429R1 |
| EAN | 8015644772796 |
| Catalog Description | E6.2X/MS 6300 3p F HR |
| Long Description | C.BREAKER SWITCH-DISCONNECTOR SACE EMAX2 E6.2X/MS 6300 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL |

### ABB EcoSolutions

| | |
|---|---|
| ABB EcoSolutions | Yes |

### Circular Value

| | |
|---|---|
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 77 % |
| Conflict Minerals Reporting Template | 9AKK108467A5658 |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| (CMRT) | |
| End of Life Instructions | 9AKK108468A2364 |
| Group Waste to Landfill Target | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

## Eco Transparency

| | |
|---|---|
| Environmental Product Declaration - EPD | 9AKK108468A1905<br>9AKK108468A1913 |

## Environmental

| | |
|---|---|
| Environmental Information | 9AKK108467A6707 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Ordering

| | |
|---|---|
| EAN | 8015644772796 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

## Dimensions

| | |
|---|---|
| Product Net Width | 762 mm |
| Product Net Height | 371 mm |
| Product Net Depth / Length | 270 mm |
| Product Net Weight | 109 kg |

## Container Information

| | |
|---|---|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 515 mm |
| Package Level 1 Height | 610 mm |
| Package Level 1 Depth / Length | 1000 mm |
| Package Level 1 Gross Weight | 118 kg |
| Package Level 1 EAN | 8015644772796 |

## Additional Information

| | |
|---|---|
| Current Type | AC |
| Electrical Durability | Ue =< 440 V 2000 cycle<br>Ue = 500 ... 690 V 2000 cycle<br>10 cycles per hour |
| Mechanical Durability | 12000 cycle<br>60 cycles per hour |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Number of Poles | 3 |
| Power Loss | 767 W |
| Product Main Type | SACE Emax 2 |
| Product Name | Switch Disconnector |
| Product Type | Switch Disconnector |
| Rated Current ($I_n$) | 6300 A |
| Rated Voltage ($U_r$) | 690 V |
| Rated Impulse Withstand Voltage ($U_{imp}$) | 12 kV |
| Rated Insulation Voltage ($U_i$) | AC 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Short-time Withstand Current Low Voltage ($I_{cw}$) | for 1 s 120 kA<br>for 3 s 100 kA |
| Rated Uninterrupted Current ($I_u$) | 6300 A |
| Short-Circuit Performance Level | X |
| Standards | IEC |
| Sub-type | E6.2 |
| Terminal Connection Type | Rear flat Horizontal |
| Version | F |

## Certificates and Declarations

| | |
|---|---|
| Data Sheet, Technical Information | 1SDC200023D0209 |
| Declaration of Conformity - CE | 9AKK106713A5544 |
| Instructions and Manuals | 1SDH001000R0002 |

## Classifications

| | |
|---|---|
| ETIM 7 | EC000216 - Switch disconnector |
| ETIM 8 | EC000216 - Switch disconnector |
| ETIM 9 | EC000216 - Switch disconnector (low voltage) |
| Object Classification Code | Q |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |
| eClass | V11.1 : 27371403 |

© 2024 ABB. All rights reserved.

## Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.