PRODUCT-DETAILS

# E1.2B-A 1200 Ekip Touch LSI 4p F F

## E1.2B-A 1200 Ekip Touch LSI 4p F F



### General Information

| | |
|---|---|
| Extended Product Type | E1.2B-A 1200 Ekip Touch LSI 4p F F |
| Product ID | 1SDA077002R1 |
| EAN | 8015644834258 |
| Catalog Description | E1.2B-A 1200 Ekip Touch LSI 4p F F |
| Long Description | C.BREAKER SACE EMAX2 E1.2B-A 1200 UL FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LSI R 1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

### ABB EcoSolutions

| | |
|---|---|
| ABB EcoSolutions | Yes |

### Circular Value

| | |
|---|---|
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 76.4 % |
| Conflict Minerals | 9AKK108467A5658 |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Reporting Template (CMRT) | |
| End of Life Instructions | 9AKK108468A2360 |
| Group Waste to Landfill Target | UL 2799 Zero Waste To Landfill Validation available |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

## Eco Transparency

| | |
|---|---|
| Environmental Product Declaration - EPD | 9AKK108468A1901 |

## Environmental

| | |
|---|---|
| Environmental Information | 9AKK108467A6707 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Ordering

| | |
|---|---|
| Order Code US and Canada | ZABDUHBE000A000000XX |
| EAN | 8015644834258 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

## Dimensions

| | |
|---|---|
| Product Net Width | 284 mm |
| Product Net Height | 295 mm |
| Product Net Depth / Length | 184 mm |
| Product Net Weight | 11 kg |

## Container Information

| | |
|---|---|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 435 mm |
| Package Level 1 Height | 350 mm |
| Package Level 1 Depth / Length | 330 mm |
| Package Level 1 Gross Weight | 18 kg |
| Package Level 1 EAN | 8015644834258 |

## Additional Information

| | |
|---|---|
| Current Type | AC |
| Electrical Durability | Ue =< 508 V 7000 cycle<br>Ue = 508 ... 635 V 6500 cycle |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| | 30 cycles per hour |
| Mechanical Durability | 20000 cycle<br>60 cycles per hour |
| Neutral Pole Current ([% Iu]) | 100 % |
| Number of Poles | 4 |
| Power Loss | at Rated Operating Conditions per Pole 125 W |
| Product Main Type | SACE Emax 2 |
| Product Name | Air Circuit Breaker |
| Product Type | Air Circuit Breaker |
| Rated Current ($I_n$) | 1200 A |
| Rated Voltage ($U_r$) | 600 V |
| Rated Insulation Voltage ($U_i$) | AC 635 V |
| Rated Operational Voltage | 600 V AC |
| Release | Ekip Touch LSI |
| Release Type | EL |
| Short-Circuit Performance Level | B |
| Standards | UL |
| Sub-type | E1.2 |
| Terminal Connection Type | Front |
| Version | F |

## Technical UL/CSA

| | |
|---|---|
| Interrupting Rating acc. to UL1066 | (254 V) 42 kA<br>(508 V) 42 kA<br>(635 V) 42 kA |

## Certificates and Declarations

| | |
|---|---|
| Data Sheet, Technical Information | 1SXU200040C0201 |
| Declaration of Conformity - CE | 9AKK106713A5546 |
| Instructions and Manuals | 1SDH000999R0002 |
| Instructions and Manuals (Part 2) | 1SDH001316R1002 |

## Classifications

| | |
|---|---|
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4926 >> Air circuit breakers |
| UNSPSC | 39121615 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27370409 |

© 2024 ABB. All rights reserved.

## Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.