PRODUCT-DETAILS

# MLP46-2-A

## SHRINK-KON 25X1,2M RED



### General Information

| | |
|---|---|
| Extended Product Type | MLP46-2-A |
| Product ID | 7TCA017300R0462 |
| EAN | 5414363105329 |
| Catalog Description | SHRINK-KON 25X1,2M RED |
| Long Description | Heat Shrink Tubing, Flexible for High Specifications, UL/CSA Listed, Thin Wall, Shrink Ratio 2:1, 3/64 Inch/1.2mm Expanded Diameter, Red, 25 X 1.22M Lengths |

### Ordering

| | |
|---|---|
| EAN | 5414363105329 |
| UPC | 786210557939 |
| Country of Origin | Germany (DE) |
| Selling Unit of Measure | each |

### Dimensions

| | |
|---|---|
| Product Net Depth / Length | 4 ft<br>1.22 m |

© 2024 ABB. All rights reserved.

## Container Information

| | |
|---|---|
| Package Level 1 Units | 25 piece |
| Package Level 1 Width | 1.9 in<br>48 mm |
| Package Level 1 Height | 1.8 in<br>46 mm |
| Package Level 1 Depth / Length | 49.3 in<br>1252 mm |

## Additional Information

| | |
|---|---|
| Brand / Label | Shrink-Kon |
| Color | Red |
| Effective Date | 19980621 |
| Flammability Hazard Rating | Flame Retardant |
| Process Temperature Rating | -67 to +212 °F<br>-55 to +100 °C |
| Product Name | Plastic conduit |
| Product Type | Thin-Wall Heat Shrinkable Tubing |
| RoHS Date | 9AKK108466A3883 |
| Shrink Ratio | 2:1 |
| Shrink Temperature | 194 °F<br>90 °C |
| Thickness | Thin |

## Certificates and Declarations

| | |
|---|---|
| Data Sheet, Technical Information | MLP46-2-A |

## Classifications

| | |
|---|---|
| ETIM 6 | EC000217 - Shrink tubing |
| ETIM 7 | EC000217 - Shrink tubing |
| ETIM 8 | EC000217 - Shrink tubing |
| UNSPSC | 39121723 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5073 >> Heat shrinkable tube |

© 2024 ABB. All rights reserved.

## Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink



© 2024 ABB. All rights reserved.