
PRODUCT-DETAILS

S804PV-SP13

S804PV-SP13 High Performance MCB



General Information

Extended Product Type	S804PV-SP13
Product ID	2CCF019623R0001
EAN	7612271471712
Catalog Description	S804PV-SP13 High Performance MCB
Long Description	The S804PV-SP13 is a 4-pole High Performance Circuit breaker for photovoltaics (DC) with B-characteristic, with cage terminal and a rated current of 13 A. It is a current limiting device with a maximum breaking capacity of 5kA at 1500V. It can be used for voltages up to 1500V DC. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S804PV-SP13 complies with IEC/EN 60947-2 Annex P and allows the use for industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S804PV-SP13 more comfortable. Due to the fast arc extinction of S804PV-SP13 your application will be secured.

Technical

Standards	IEC/EN 60947-2
Tripping Characteristic	B
Rated Voltage (U_r)	acc. to IEC 60947-2 1500 V DC
Rated Operational Voltage	acc. to IEC 60898-1 400 V
Rated Insulation Voltage	acc. to IEC/EN 60664-1 1500 V

© 2024 ABB. All rights reserved.

(U_i)	
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Input Voltage Type	DC
Rated Current (I_n)	13 A
Rated Operational Current (I_e)	13 A
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(1500 V DC) 5 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(1500 V DC) 5 kA
Frequency (f)	0...0 Hz
Rated Frequency (f)	0 Hz
Power Loss	8 W at Rated Operating Conditions per Pole 2 W
Energy Limiting Class	3
Number of Protected Poles	4
Number of Poles	4
Overvoltage Category	III
Release Type	SP
Accessories Available	Yes
Connecting Capacity	Flexible 0 … 50 mm² Rigid 0 … 70 mm²

Material Compliance

RoHS Information	9AKK107680A3903 2CCC005084D0202
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20170426
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Temperature	-25...60 °C
Ambient Air Temperature	Operation -25 … 60 °C
Degree of Protection	IP20
Pollution Degree	2
Environmental Information	2CCY413207D0203

Dimensions

Width in Number of Modular Spacings	6
Product Net Width	106 mm
Product Net Height	95 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	980 g
Built-In Depth (t_2)	111 mm

Ordering

Package Level 1 Units	box 1 piece

© 2024 ABB. All rights reserved.

Package Level 1 Gross Weight	1010 g
E-Number (Finland)	3214019

Certificates and Declarations

Declaration of Conformity - CE	2CCC005084D0202

Installation

Instructions and Manuals	2CCC413016M0008

Popular Downloads




Data Sheet, Technical Information	9AKK108468A9560 9AKK108468A9561 9AKK108468A9562

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020
eClass	V11.0 : 27141901
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs

© 2024 ABB. All rights reserved.