PRODUCT-DETAILS

# SPB50/10M

## STEEL BRDD SP LIQ.PROOF NC50 10MT



### General Information

| | |
|---|---|
| Extended Product Type | SPB50/10M |
| Product ID | 7TCA296040R0161 |
| EAN | 5020963006289 |
| Catalog Description | STEEL BRDD SP LIQ.PROOF NC50 10MT |
| Long Description | Highly Flexible Steel Conduit, Nominal Conduit Size 50mm, Outer Diameter 56.0mm, Inner Diameter 48.4mm, Maximum Bend Radius 90mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid |

### Additional Information

| | |
|---|---|
| Application | Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance |
| Product Type | High Flexibility Conduit |

### Ordering

| | |
|---|---|
| EAN | 5020963006289 |
| UPC | 786210274706 |

© 2024 ABB. All rights reserved.

## Dimensions

| | |
|---|---|
| Product Net Depth / Length | 10 m |

## Technical

| | |
|---|---|
| Number of Batteries | 0 |
| Material | Galvanized Steel Core and Overbraid with PVC Jacket |

## Environmental

| | |
|---|---|
| WEEE Category | Product Not in WEEE Scope |

## Container Information

| | |
|---|---|
| Package Level 1 Units | 1 piece |
| Package Level 1 Height | 9.37 in<br>238 mm |
| Package Level 1 Depth / Length | 19.25 in<br>489 mm |
| Package Level 1 Width | 19.25 in<br>489 mm |

## Certificates and Declarations

| | |
|---|---|
| Data Sheet, Technical Information | SPB50/10M |
| Instructions and Manuals | SPB50/10M |
| Declaration of Conformity - CE | 9AKK107492A9618 |
| RoHS Information | 9AKK107992A8994 |
| RoHS Date | 9AKK107992A8994 |
| REACH Declaration | 9AKK107992A8994 |

## Classifications

| | |
|---|---|
| ETIM 8 | EC001179 - Protective metallic hose |
| UNSPSC | 39131706 |

© 2024 ABB. All rights reserved.

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



© 2024 ABB. All rights reserved.