SCHEDINA TECNICA - THYRISTOR FUSE 1000A 690V



Cartuccia fusibile, corsa rapida, 1000 A, AC 690 V, 78 x 64 mm, gL/gG, BS, IEC

Powering Business Worldwide

Tipo	**THYRISTOR FUSE 1000A 690V**
Catalog No.	**1000F4M**

Abbildung ähnlich

Programma di fornitura

Assortimento			fusibile
Funzione di base			cartuccia fusibile
campo di validità			corsa rapida
Corrente nominale d'impiego	I	A	1000
Tensione nominale d'impiego			AC 690 V
Grandezza			78 x 64 mm
Classe di funzionamento			gL/gG
Utilizzo			protezione tiristore
Standard/Approvazione			BS IEC
Forma			Contatto terminale a filo
Standard/Norme			BS88-4 IEC 60269-4

Dati tecnici secondo ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			Other
Nominal rated current		A	1000
Nominal rated voltage		V	690
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			None

© 04/2022 by Eaton Industries GmbH