SCHEDINA TECNICA - C10-SLS/32/2



Sezionatore con fusibili, 32A, 2p, 10x38

Tipo	**C10-SLS/32/2**
Catalog No.	**112222**

Powering Business Worldwide™

Dati tecnici secondo ETIM 6.0

Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss8.1-27-37-14-01 [AKF058010])

Version as main switch			No
Version as safety switch			No
Max. rated operation voltage Ue AC		V	690
Rated permanent current Iu		A	32
Rated operation power at AC-23, 400 V		kW	0
Conditioned rated short-circuit current Iq		kA	100
Rated short-time withstand current Icw		kA	0.3
Suitable for fuses			Shape C1-C3
Number of poles			2
With error protection			No
Type of electrical connection of main circuit			Screw connection
Suitable for ground mounting			Yes
Suitable for front mounting 4-hole			No
Suitable for busbar mounting			No
Type of control element			Other
Position control element			Front side
Motor drive optional			No
Motor drive integrated			No
Version as emergency stop installation			No
Degree of protection (IP), front side			IP20

© 04/2022 by Eaton Industries GmbH