

Specifications

Eaton CCP2-2-30M

Eaton Bussmann series CCP UL98 fusible disconnect, 30A, UL98 fusible disconnect, Two-pole, 60 Hz, Supplemental, 120 - CCP2-2-30M

General specifications

PRODUCT NAME	Eaton Bussmann series CCP UL98 fusible disconnect
CATALOG NUMBER	CCP2-2-30M
UPC	051712709200
PRODUCT LENGTH/DEPTH	4.5 in
PRODUCT HEIGHT	3.1 in
PRODUCT WIDTH	1.4 in
PRODUCT WEIGHT	1.46 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	UL Recognized

Electrical rating

AMPERAGE RATING	30A
FREQUENCY RATING	50/60 Hz
SHORT-CIRCUIT RATING	120 kA
VOLTAGE RATING	400 Vac, 80 Vdc

General information

SPECIAL FEATURES	Finger Safe, 1/4" LOTO
------------------	------------------------

Physical details

FUSE TYPE	Supplemental
NUMBER OF POLES	Two-pole

Resources

CATALOGS	CCP2-2-30M~2 Pole Comp Ckt Protect 30A
	Bussmann series complete full line catalog no. 1007
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CCP2-2-30M

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

