

Specifications

Eaton LP-CC-1

Eaton Bussmann Series Class CC fuse, LP-CC, time-delay, dual-element current limiting fuse, 1 A, rejection style fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series LP-CC fuse
CATALOG NUMBER	LP-CC-1
UPC	051712180436
EAN	5027590446914
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	1.5 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.15 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant

Product specifications

AMPERAGE RATING	1 A
NUMBER OF ELEMENTS	Dual
CLASS	Class CC
INTERRUPT RATING	200 kAIC at 600 Vac 20 kAIC at 300 Vdc
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	12 sec at 200%
MATERIAL	Melamine tube
PACKAGING TYPE	Standard
QUANTITY	10
VOLTAGE RATING	600 Vac, 300 Vdc
TYPE	Current-limiting time-delay fuse
SPECIAL FEATURES	Non-indicating
APPLICATION	Specialized circuits and industrial control

Resources

	LP-CC-1~LOW PEAK CC TIME DELAY
	Bussmann series full line catalog 1007, section 01-low voltage branch circuit fuses
	Bussmann series complete full line catalog no. 1007
CATALOGS	
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2000
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - LP-CC-1
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

