
BARRA DI TERRA, NUDA, 14 CONNECTIONS, 1 NUMERO DI DISCONNESSIONI, 925 MM

CATALOG NUMBER

EEB14C506D1A



FEATURES

- Fornisce una comoda e unica posizione di messa a terra e collegamento
- Barra di terra con collegamenti di disconnessione per testare il sistema di messa a terra
- High conductivity, hard drawn, electrolytic tough pitch copper per EN 13601
- Includes halogen-free polyamide insulators, stainless steel (EN 1.4401) hardware and mounting brackets
- È possibile la progettazione e la produzione di barre personalizzate in base alle specifiche del cliente

CARATTERISTICHE DEL PRODOTTO


- Complies With: IEC® EN 62561-1:2017 Classe H
- Material: Rame
- Finish: Nuda
- Number of Connections: 14
- Number of Disconnects: 1
- Thread Size (TS): M10
- Height (H): 94 mm
- Length (L): 925 mm
- Width 1 (W1): 100 mm
- Width 2 (W2): 50 mm
- Thickness (T): 6 mm
- A: 50 mm

Unit Weight: 4,36 kg

ADDITIONAL PRODUCT DETAILS

Tinned finish is 8 microns according to ASTM B545 Service Class "C" for corrosive environments.

DIAGRAMS



AVVERTENZA

AVVERTENZA: i prodotti nVent devono essere installati e usati solo secondo le indicazioni riportate nei fogli delle istruzioni del prodotto nVent e nei materiali di formazione. I fogli di istruzioni sono disponibili sul sito www.nvent.com e presso il vostro rappresentante locale dell'assistenza clienti di nVent. Un'installazione scorretta, l'uso improprio, l'applicazione errata o altre inosservanze delle istruzioni e delle avvertenze di nVent possono causare un malfunzionamento del prodotto, danni alle proprietà, lesioni corporee gravi e morte e/o l'annullamento della garanzia.

America del Nord
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.