
Pendelleuchte | 1176 topLED 224 W DC 24 V | CRI 80

65322W00



Technische Daten	
Typ	Oberfläche
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward and upward
Lampe Nennleistung	224 W DC
Lichtstrom (Lichtquelle)	31176 lm
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP40
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	Ja
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	5 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	19.9 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein
Optiktechnologie	Dot free

Oberfläche Oberfläche Gehäuse	
Material	Aluminiumlegierung 6060
Farbe	Burnished
Bearbeitungstyp	Flüssiglackierung

Oberfläche Oberfläche diffusor	
Material	UV beständiges Polycarbonat
Farbe	Opal

Elektronik



99786
On/Off Driver 180~295V AC / V DC (1 art.)



99787
DALI Controller 100~305V AC / 142~431V DC 240 W (1 art.)

Cables Electrification	
Cable connector	No
Cable connector	No
Cable connector	No

Cables Pendelleuchte	
Max. Kabellänge	5000 mm
Max. Kabellänge	5000 mm

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Pendelleuchte | 1176 topLED 224 W DC 24 V | CRI 80
65322W00

Double emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 1176 topled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 31176 lm, with a 139.2 lm/W nominal luminous efficacy.


The device body is made of aluminium alloy 6060 and features a burnished finish, processed by means of liquid painting; the diffuser is made of uv resistant polycarbonate.


The ingress protection degree is IP40; the total weight is of 19.9 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 224 W The power supply cable is included and features a 5 m length.

The device features protection class III and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält 54 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	53 %
Lichtstrom (Lichtquelle)	31176 lm
Leuchten Lichtstrom	16716 lm
Consumption	224 W
Leuchten Lichtausbeute	74 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B10 C0 494435h (at Tj 65 Ta 25)
L80 B10 C0 310287h (at Tj 65 Ta 25)
L90 B10 C0 147856h (at Tj 65 Ta 25)


UGR	
UGR axial	14.1
UGR transversal	14.4
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	154°
Light distribution simmetry	Symmetrical

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Tour_D | Pendant Luminaires | Accessories
65322W00






Hängeleuchten - Befestigungssatz
Material:Aluminiumlegierung 6026, farbe:Burnished, bearbeitungstyp :Flüssiglackierung.

Code
64673






Deckenrosette - On/off - Max 150+150W
Einschließlich Driver: Ja; Netzteil-Verwaltungsprotokoll: On/off; Maximale Leistung: 150+150W.
Material:Eisen, farbe:Burnished, bearbeitungstyp :Flüssiglackierung.

Code
65344





Deckenrosette - DALI - Max 150+150W
Einschließlich Driver: Ja; Netzteil-Verwaltungsprotokoll: Dali; Maximale Leistung: 150+150W.
Material:Eisen, farbe:Burnished, bearbeitungstyp :Flüssiglackierung.

Code
65345

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.