
Uplights - Step-Leuchten
1 x powerLEDs 4.5 W DC 500 mA | CRI 80
**76865W18**




| Technische Daten | |
|---|---|
| Typ | Halbeinbau - Step- |
| Installationsposition | Boden |
| Installationsumgebung | Outdoor |
| Lichtquelle | LED |
| Circuit structure | powerLEDs |
| Optik | Radial Multidirectional emission |
| Light emission direction | external |
| Lampe Nennleistung | 4.5 W DC |
| Lichtstrom (Lichtquelle) | 575 lm |
| Eingangsspannungsbereich | 500mA |
| Ähnlichste Farbtemperatur / Tone | 3000 K |
| Farbwiedergabeindex | 80 Ra |
| Gleichstrom/Gleichspannung | CC |
| Isolierklasse | 3 |
| IP | IP67 |
| IK | IK10 |
| Glühdrahtprüfung | 850° |
| Direkte Montage auf normal entflammbaren Oberflächen | Ja |
| CE | Ja |
| Einschließlich Driver | Nein |
| Leuchte dimmbar | Ja |
| Schwenkbarkeit | Nein |
| Drehbarkeit | Nein |
| Begehbarkeit | Ja |
| Überrollbarkeit | 1500 Kg |
| Einschließlich Kabel | Ja |
| Kabellänge | 1 m |
| Harzbeschichtung | Ja |
| Einbautiefe | 65 mm |
| Typ Lichtabstrahlung | Mehrflammig |
| Nettogewicht | 0.3 Kg |
| Schutz vor elektrostatischen Entladungen | Nein |
| Schutz vor Stoßspannungen | Nein |
| Technische Merkmale des Produkts | Acquastop |

| Oberfläche Oberfläche Gehäuse | |
|---|---|
| Material | Aluminium |
| Farbe | Black |
| Bearbeitungstyp | Offenporige Anodisierung + Pulverlackierung |

| Oberfläche Oberfläche flansch | |
|---|---|
| Material | Aluminiumlegierung 6026 |
| Farbe | Text brilliant grey RAL 9006 |
| Bearbeitungstyp | Offenporige Anodisierung + Pulverlackierung |

**Elektronik**



99185
On/Off Driver 198~264V AC (2 - 4 art.)



C-E200003
Push and Simply Dim - DALI-2 Controller (1 - 4 art.)



C-E200007
On/Off Driver 198~264V AC / V DC (1 - 2 art.)

| Cables Electrification | |
|---|---|
| Cable connector | No connector - Neoprene 2x1mm² |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Uplights - Step-Leuchten | 1 x powerLEDs 4.5 W DC 500 mA | CRI 80
**76865W18**

Multiple emission uplights for outdoor application. The warm white LED light source with a radial multidirectional emission light distribution is composed of 1 powerled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 575 lm, with a 127.8 lm/W nominal luminous efficacy.


The device body is made of aluminium and features a black finish, processed by means of open pore anodizing + powder coating. Surface treatment of the product body through aluminum chemical conversion, followed by polyester powder coating, using exclusively coatings compliant with the Qualicoat standard.The aluminum flange is treated with a chemical conversion process to ensure maximum paint adhesion and corrosion protection, followed by polyester powder coating using exclusively coatings compliant with the Qualicoat standard.

The ingress protection degree is IP67; the total weight is of 0.3 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 4.5 W The power supply cable is included and features a 1 m length.

The device features protection class III and can be floor-mounted with an outer casing, code 84936(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.




| Energieeffizienzklasse |
|---|
| Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E. |

| Illuminotechnical Eigenschaften | |
|---|---|
| Light Output Ratio (LOR) | 22 % |
| Lichtstrom (Lichtquelle) | 575 lm |
| Leuchten Lichtstrom | 128 lm |
| Consumption | 4.5 W |
| Leuchten Lichtausbeute | 28 lm/W |
| Farbtemperatur | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Farbwiedergabeindex | 80 Ra |
| Standardumgebungstemperatur | -20 / +50°C |
| Typische Temperatur am Glas | 40°C |

| LED Life / Failure Ratio |
|---|
| L70 B10 C0 363000h (at Tj 65  Ta 25 ) |
| L80 B10 C0 237566h (at Tj 65  Ta 25 ) |
| L90 B10 C0 151000h (at Tj 65  Ta 25 ) |

| OPTICAL | |
|---|---|
| Optik C0/C180 | 180° |
| Light distribution simmetry | Symmetrical |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Alcor_R4 | Step Lights | Accessories
**76865W18**






Einbaugehäuse

installationsposition: boden; typ installation: mauerwerk L=92mm, H=69mm, D=69mm.

Material:Kunststoff ABS, farbe:Black.

| Code |
| --- |
| 84936 |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.