
Ink system_L UGR

Systeme - Lineare Elemente
36 topLED 14 W DC 24 V | CRI 90
77586M30







Technische Daten	
Jahr der Verwirklichung	2019
Typ	Lineare Elemente
Installationsposition	Kabel
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Medium Flood
Light emission direction	downward
Lampe Nennleistung	14 W DC
Lichtstrom (Lichtquelle)	1217 lm
Frequency	50-60 Hz
Ähnlichste Farbtemperatur / Tone	2700 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP40
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V - PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.315 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein
Optiktechnologie	Dark light

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	Text white RAL9003
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	PC
Bearbeitungstyp	Lackierung

Elektronik



81416
On/Off Driver 220~240V AC 120 W (1 - 8 art.)



83041
1-10V - Push and Simply Dim - DALI-2 Controller (1 - 4 art.)



81417
On/Off Driver 220~240V AC 180 W (1 - 12 art.)



83042
1-10V - Push and Simply Dim - DALI-2 Controller (- art.)



83415
On/Off Driver 220~240V AC 120 W (1 - 8 art.)



83416
On/Off Driver 220~240V AC 180 W (1 - 12 art.)



83429
On/Off Driver 220~240V AC 120 W (1 - 8 art.)



83431
On/Off Driver 220~240V AC 180 W (1 - 12 art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme - Lineare Elemente | 36 topLED 14 W DC 24 V | CRI 90
77586M30

Single emission systems or lines for indoor application. The super warm white LED light source with a medium flood light distribution is composed of 36 topled LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 1217 lm, with a 86.9 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a text white ral9003 finish, processed by means of coating; the diffuser is made of PC with a coating treatment.

The ingress protection degree is IP40; the total weight is of 0.315 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 14 W

The device features protection class III and can be cable-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.


Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F.


Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	40 %
Lichtstrom (Lichtquelle)	1217 lm
Leuchten Lichtstrom	494 lm
Consumption	14 W
Leuchten Lichtausbeute	35 lm/W
Farbtemperatur	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B10 C0 102000h
L90 B10 C0 55000h

UGR	
UGR axial	3.6
UGR transversal	10.6
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	34°
Optik C0/C180	39°
Light distribution simmetry	Symmetrical 2 assis





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L UGR | Lines | Accessories
77586M30



Kabel
Typ Kabel power cable; Länge 5000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: weiß - rot.

Code
83412



Kabel
Typ Kabel power cable; Länge 10000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: weiß - rot.

Code
83413



Kabel
Typ Kabel power cable; Länge 1000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: schwarz - rot.

Code
83414





Profil - Kit 5 x
Material:Aluminium, bearbeitungstyp :Lackierung.


Code
81426





Profil - Kit 2 x
Material:Aluminium, bearbeitungstyp :Lackierung.


Code
81430



Drahtabdeckung
Material:PC, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83417





Kabelverbindung
Typ linear.
Material:PC, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83418





Kabelverbindung
Typ linear.
Material:PC, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83419

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L UGR | Lines | Accessories
77586M30





Kabelverbindung
Typ linear.
Material:PC, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.


Code
83420



Endkappe
Material:PC, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83421






Profil
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
84010





Profil
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
84011






Klammer - 2X
installationsposition: wand, decke.
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.


Code
83422






Drahtabdeckung - 2X
Material:Eisen, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83423





Drahtabdeckung - 2X
Material:PC, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83424






Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83425

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L UGR | Lines | Accessories
77586M30





Lochschablone
Material:Eisen, bearbeitungstyp :Lackierung.

Code
83186






Werkzeug - Set zum Schneiden/Abisolieren von Kabeln
Material:Stahl, farbe:Stahl.

Code
81427





Kabel für Aufhängung
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
83427

Schiene
Länge: 1000mm.
Material:Aluminium, farbe:weiß RAL 9003, bearbeitungstyp :Lackierung.

Code
83433

Schiene
Länge: 2000mm.
Material:Aluminium, farbe:weiß RAL 9003, bearbeitungstyp :Lackierung.

Code
83435

Kabelverbindung
Material:Aluminium, farbe:weiß RAL 9003, bearbeitungstyp :Lackierung.

Code
83437

Kabelverbindung
Material:Aluminium, farbe:weiß RAL 9003, bearbeitungstyp :Lackierung.

Code
83439

Kabelverbindung
Material:Aluminium, farbe:weiß RAL 9003, bearbeitungstyp :Lackierung.

Code
83441

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L UGR | Lines | Accessories
77586M30

	Code
Kabelverbindung	83442
Kabel für Aufhängung Material:Aluminium, farbe:weiß RAL 9003, bearbeitungstyp :Lackierung.	83444
Kabel Länge 1000 mm; farben: schwarz.	83445
Kabel Länge 1000 mm; farben: schwarz.	83446

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.