

Systeme - Lineare Elemente
72 topLED 22 W DC 24 V | CRI 90
82916M00







Technische Daten	
Jahr der Verwirklichung	2019
Typ	Lineare Elemente
Installationsposition	Kabel
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	22 W DC
Lichtstrom (Lichtquelle)	1976 lm
Frequency	50-60 Hz
Ähnlichste Farbtemperatur / Tone	2700 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP40
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V - PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.315 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	PC
Farbe	Opal

Elektronik


81416
On/Off Driver 220~240V AC 120 W (1 - 5 art.)


83041
1-10V - Push and Simply Dim - DALI-2 Controller (1 - 2 art.)


81413
On/Off Driver 220~240V AC 120 W (1 - 5 art.)


81414
On/Off Driver 220~240V AC 180 W (1 - 8 art.)


81417
On/Off Driver 220~240V AC 180 W (1 - 8 art.)


83042
1-10V - Push and Simply Dim - DALI-2 Controller (- art.)


83428
On/Off Driver 220~240V AC 120 W (1 - 5 art.)


83430
On/Off Driver 220~240V AC 180 W (1 - 8 art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme - Lineare Elemente | 72 topLED 22 W DC 24 V | CRI 90
82916M00

Single emission systems or lines for indoor application. The super warm white LED light source with a diffused light distribution is composed of 72 topled LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 1976 lm, with a 89.8 lm/W nominal luminous efficacy.


The device body is made of aluminium and features a 5g 9005 black finish, processed by means of coating; the diffuser is made of PC.


The ingress protection degree is IP40; the total weight is of 0.315 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 22 W

The device features protection class III and can be cable-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse F.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	38 %
Lichtstrom (Lichtquelle)	1976 lm
Leuchten Lichtstrom	751 lm
Consumption	22 W
Leuchten Lichtausbeute	34 lm/W
Farbtemperatur	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B10 C0 102000h (at Tj 115 Ta 25)
L90 B10 C0 55000h

UGR	
UGR axial	26.4
UGR transversal	28.6
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	105°
Optik C0/C180	119°
Light distribution simmetry	Symmetrical 2 assis

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L | Lines | Accessories
82916M00






Profil - Kit 2 x
Material:Aluminium, bearbeitungstyp :Lackierung.


Code
81430






Drahtabdeckung - Abzweigdose schwarz
Material:PC, bearbeitungstyp :Lackierung.


Code
81424





Kabelverbindung
Typ linear.
Material:PC, bearbeitungstyp :Lackierung.


Code
81418





Kabelverbindung - L-Verbindungsstück schwarz, elektrifiziert
Typ linear.
Material:PC, bearbeitungstyp :Lackierung.


Code
81419





Kabelverbindung
Typ linear.
Material:PC, bearbeitungstyp :Lackierung.

Code
81420






Endkappe - Verschlusskappe schwarz, elektrifiziert
Material:PC, bearbeitungstyp :Lackierung.

Code
81421






Profil
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
84010





Profil
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
84011

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L | Lines | Accessories
82916M00






Klammer - 2X
installationsposition: wand, decke.
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
84017






Drahtabdeckung - 2X
Material:Eisen, bearbeitungstyp :Lackierung.

Code
81422






Drahtabdeckung - 2X
Material:PC, bearbeitungstyp :Lackierung.

Code
81423






Kabel für Aufhängung
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
81425





Lochschablone
Material:Eisen, bearbeitungstyp :Lackierung.

Code
83186





Werkzeug - Set zum Schneiden/Abisolieren von Kabeln
Material:Stahl, farbe:Stahl.

Code
81427





Kabel für Aufhängung
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
83426

Schiene
Länge: 1000mm.
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
83432

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L | Lines | Accessories
82916M00

	Code
Schiene Länge: 2000mm. Material:Aluminium, bearbeitungstyp :Lackierung.	83434
Kabelverbindung Material:Aluminium, bearbeitungstyp :Lackierung.	83436
Kabelverbindung Material:Aluminium, bearbeitungstyp :Lackierung.	83438
Kabelverbindung Material:Aluminium, bearbeitungstyp :Lackierung.	83440
Kabelverbindung	83442
Kabel für Aufhängung Material:Aluminium, bearbeitungstyp :Lackierung.	83443
Kabel Länge 1000 mm; farben: schwarz.	83445
Kabel Länge 1000 mm; farben: schwarz.	83446

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L | Lines | Accessories
82916M00





Profil - Kit 5 x
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
81426





Kabel
Typ Kabel power cable; Länge 1000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: schwarz - rot.

Code
84016





Kabel
Typ Kabel power cable; Länge 10000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: schwarz - rot.

Code
81411





Kabel
Typ Kabel power cable; Länge 5000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: schwarz - rot.

Code
81410

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.