
Trail_line 7 poles

Systeme | 220-240 V AC /176-276 V DC
topLED 54 W DC - 60 W AC | Modular | CRI 80
83656N00







Technische Daten	
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	54 W DC
Gesamtleistung	60 W
Lichtstrom (Lichtquelle)	7522 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	4000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	DALI
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	1.800 Kg
Modularity	Modular
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	Text black RAL9005
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	PMMA

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 220-240 V AC /176-276 V DC | topLED 54 W DC - 60 W AC | Modular | CRI 80
83656N00

Single emission systems for indoor application. The natural white LED light source with a diffused light distribution is composed of 120 topled LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 7522 lm, with a 139.3 lm/W nominal luminous efficacy.


The device body is made of aluminium and features a text black ral9005 finish, processed by means of coating; the diffuser is made of pmma.


The ingress protection degree is IP20; the total weight is of 1.800 kg.

The total absorbed power is 60 W

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	70 %
Lichtstrom (Lichtquelle)	7522 lm
Leuchten Lichtstrom	5329 lm
Consumption	60 W
Leuchten Lichtausbeute	88 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25°C

LED Life / Failure Ratio
L70 B20 C0 36000h

UGR	
UGR axial	26.7
UGR transversal	29.5
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20


OPTICAL	
Optik C90/C270	110°
Optik C0/C180	136°
Light distribution simmetry	Symmetrical 2 assis

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 220-240 V AC /176-276 V DC | topLED 54 W DC - 60 W AC | Modular | CRI 80
83656N00

Components






Trail Power Module backbone 7 poles ON/OFF DALI - Sistemi

Code
83651






Trail Power Module backbone 7 poles ON/OFF DALI - Sistemi

Code
83652






Trail standard backbone 7 poles ON/OFF DALI

Code
83653





Trail standard backbone 7 poles ON/OFF DALI

Code
83654






Trail Three-phase adapter - Sistemi

Code
83067






Trail Auxiliary power backbone 7 poles ON/OFF

Code
83655

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Trail_line 7 poles | Systems | Accessories
83656N00






Kabel für Aufhängung

Code
90944





Kabel für Aufhängung

Code
90943






Klammer
L=53mm, H=13mm, D=23mm

Code
90945





Endkappe
Material:Aluminium, farbe:weiß RAL 9003, bearbeitungstyp :Lackierung.

Code
90946



Profil
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
90950

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.