
Blum Flower

Poller & Mastaufsatzleuchten
180-264 V AC /230-280 V DC | 3 x powerLED 4.5 W DC - 5.5 W AC | CRI 80
83882A00

MARINE GRADE





Technische Daten	
Typ	Poller
Installationsposition	Boden
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	powerLED
Optik	Diffuses
Light emission direction	frontal
Lampe Nennleistung	4.5 W DC
Gesamtleistung	5.5 W
Lichtstrom (Lichtquelle)	450 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	180 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	2200 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP65
IK	IK08
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Orientabile tramite flessibile
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Ja
Typ Lichtabstrahlung	Mehrflammig
Nettogewicht	0.780 Kg
Schutz vor elektrostatischen Entladungen	0.5 KV
Schutz vor Stoßspannungen	Ja
Optiktechnologie	Optilight TM

Oberfläche Oberfläche Gehäuse	
Farbe	Braun

Oberfläche Oberfläche diffusor	
Material	Polymethylmethacrylat UV-beständige
Farbe	Transparent
Bearbeitungstyp	Lasersiebdruck

Oberfläche Oberfläche sockel	
Material	Kunststoff ABS
Farbe	Braun
Bearbeitungstyp	Lackierung

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Poller & Mastaufsatzleuchten | 180-264 V AC /230-280 V DC | 3 x powerLED 4.5 W DC - 5.5 W AC | CRI 80

83882A00

Multiple emission bollard & pole for outdoor application. The ancient white LED light source with a diffused light distribution is composed of 3 powerled LEDs with CCT of 2200 K and a CRI 80; the source luminous flux is 450 lm, with a 100.0 lm/W nominal luminous efficacy.

Product suitable for installations in coastal areas with high salinity and strong exposure to atmospheric agents.

The device body and features a brown finish; the diffuser is made of uv resistant polymethylmethacrylate with a laser screen printing treatment.

The ingress protection degree is IP65; the total weight is of 0.780 kg.

The total absorbed power is 5.5 W

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält 3 Lichtquellen der Energieeffizienzklasse F.


Illuminotechnical Eigenschaften	
Lichtstrom (Lichtquelle)	450 lm
Farbtemperatur	2200 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B10 C0 214455h (at Tj 65 Ta 25)
L80 B10 C0 136355h (at Tj 65 Ta 25)
L90 B10 C0 67466h (at Tj 65 Ta 25)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Blum Flower | Bollard & Pole | Accessories
83882A00





Erdspießen
installationsposition: terreno,Material Verkleidung: uv beständiges polycarbonat

Code
14931



Diffusor - Geschlossener Blütendiffusor für Blum Flower
Diffusorart: optilight technology.
Material:Polymethylmethacrylat UV-beständige, farbe:Transparent, bearbeitungstyp :Lasersiebdruck.

Code
83883



Diffusor - Offener Blütendiffusor für Blum Flower
Diffusorart: optilight technology.
Material:Polymethylmethacrylat UV-beständige, farbe:Transparent, bearbeitungstyp :Lasersiebdruck.

Code
83884

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.