
Downlights | 1 x powerLED 2 W DC 630 mA | CRI 80

**85062W12**






| Technische Daten | |
|---|---|
| Installationsposition | Wand - Decke |
| Installationsumgebung | Indoor |
| Lichtquelle | LED |
| Circuit structure | powerLED |
| Optik | Extra Wide Flood |
| Lampe Nennleistung | 2 W DC |
| Lichtstrom (Lichtquelle) | 233 lm |
| Eingangsspannungsbereich | 630mA |
| Ähnlichste Farbtemperatur / Tone | 3000 K |
| Farbwiedergabeindex | 80 Ra |
| Gleichstrom/Gleichspannung | CC |
| Isolierklasse | 3 |
| IP | IP44 |
| Glühdrahtprüfung | 850° |
| Direkte Montage auf normal entflammbaren Oberflächen | Ja |
| CE | Ja |
| Einschließlich Driver | Nein |
| Leuchte dimmbar | DALI - 1-10V |
| Schwenkbarkeit | Nein |
| Drehbarkeit | Nein |
| Begehbarkeit | Nein |
| Überrollbarkeit | Nein |
| Einschließlich Kabel | Ja |
| Kabellänge | 0.12 m |
| Harzbeschichtung | Ja |
| Einbautiefe | 45 mm |
| Typ Lichtabstrahlung | Einflammig |
| Nettogewicht | 0.073 Kg |
| Schutz vor elektrostatischen Entladungen | Nein |
| Schutz vor Stoßspannungen | Nein |

| Oberfläche Oberfläche Gehäuse | |
|---|---|
| Material | Messing gebürstet |
| Farbe | Brushed nickel |
| Bearbeitungstyp | Bürsten |

| Oberfläche Oberfläche strahler | |
|---|---|
| Material | Aluminium |
| Farbe | Anodised aluminium |
| Bearbeitungstyp | Eloxierung |

**Elektronik**



89147
On/Off Driver 198~264V AC / 180~275V DC



99105
On/Off Driver 198~264V AC



99374
On/Off Driver 198~264V AC / 176~275V DC  75 W



99710
1-10V - 0-10V Converter V DC



99713
DALI Converter V DC



99376
On/Off Driver 198~264V AC



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Downlights | 1 x powerLED 2 W DC 630 mA | CRI 80
**85062W12**

Single emission recessed downlights for indoor application. The warm white LED light source with a extra wide flood light distribution is composed of 1 powerled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 233 lm, with a 116.5 lm/W nominal luminous efficacy.


The device body is made of brass and features a brushed nickel finish, processed by means of brushing.


The ingress protection degree is IP44; the total weight is of 0.073 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 2 W The power supply cable is included and features a 0.12 m length.

The device features protection class III and can be wall lights or ceiling-mounted, with a mm diameter hole (in plasterboard) with an outer casing, code 84901(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.




| Energieeffizienzklasse |
|---|
| Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse D. |

| Illuminotechnical Eigenschaften | |
|---|---|
| Light Output Ratio (LOR) | 39 % |
| Lichtstrom (Lichtquelle) | 466 lm |
| Leuchten Lichtstrom | 182 lm |
| Consumption | 2,0 W |
| Leuchten Lichtausbeute | 91 lm/W |
| Farbtemperatur | 3000 K |
| Standard Deviation of Colour Matching | 1.5 Step |
| Farbwiedergabeindex | 80 Ra |
| Standardumgebungstemperatur | -20 / +50°C |
| Typische Temperatur am Glas | 40°C |

| LED Life / Failure Ratio |
|---|
| L70 B10 C0 1240219h (at Tj 65  Ta 25 ) |
| L80 B10 C0 745627h (at Tj 65  Ta 25 ) |
| L90 B10 C0 309367h (at Tj 65  Ta 25 ) |

| UGR | |
|---|---|
| UGR axial | 32.6 |
| UGR transversal | 32.5 |
| X=4H \| Y=8H | S=0.25H |
| Reflection factor | 70/50/20 |

| OPTICAL | |
|---|---|
| Optik C0/C180 | 112° |
| Light distribution simmetry | Symmetrical |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Nitum_Q | Downlights | Accessories
**85062W12**






Einbaugehäuse

installationsposition: decke; typ installation: mauerwerk L=69mm, H=60mm, D=60mm.

Material:Kunststoff ABS, farbe:Black.

| Code |
| --- |
| 84901 |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.