
Downlights | 1 x powerLED 1.5 W DC 500 mA | CRI 80

**85960M70**








15

| Technische Daten | |
|---|---|
| Installationsposition | Wand - Decke |
| Installationsumgebung | Indoor |
| Lichtquelle | LED |
| Optik | Medium Wide Flood |
| Lampe Nennleistung | 1.5 W DC |
| Lichtstrom (Lichtquelle) | 130 lm |
| Eingangsspannungsbereich | 500mA |
| Ähnlichste Farbtemperatur / Tone | 2700 K |
| Farbwiedergabeindex | 80 Ra |
| Gleichstrom/Gleichspannung | CC |
| Isolierklasse | 3 |
| IP | IP44 |
| Glühdrahtprüfung | 850° |
| Direkte Montage auf normal entflammbaren Oberflächen | Ja |
| CE | Ja |
| Einschließlich Driver | Nein |
| Leuchte dimmbar | DALI - 1-10V |
| Schwenkbarkeit | Nein |
| Drehbarkeit | Nein |
| Begehbarkeit | Nein |
| Überrollbarkeit | Nein |
| Einschließlich Kabel | Ja |
| Kabellänge | 0.12 m |
| Harzbeschichtung | Nein |
| Einbautiefe | 70 mm |
| Typ Lichtabstrahlung | Einflammig |
| Nettogewicht | 0.037 Kg |
| Schutz vor elektrostatischen Entladungen | Nein |
| Schutz vor Stoßspannungen | Nein |

| Oberfläche Oberfläche Gehäuse | |
|---|---|
| Material | Messing gebürstet |
| Farbe | Brushed nickel |
| Bearbeitungstyp | Bürsten |

| Oberfläche Oberfläche strahler | |
|---|---|
| Material | Aluminium |
| Farbe | Anodised aluminium |
| Bearbeitungstyp | Eloxierung |

**Elektronik**



89146
On/Off Driver 198~264V AC / 180~275V DC (2 - 3 art.)



99195
On/Off Driver 198~264V AC / 180~275V DC (1 - 2 art.)



99374
On/Off Driver 198~264V AC / 176~275V DC  75 W (- art.)



99709
1-10V - 0-10V Converter V DC (- art.)



99712
DALI Converter V DC (- art.)



99377
On/Off Driver 198~264V AC (3 - 6 art.)



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Downlights | 1 x powerLED 1.5 W DC 500 mA | CRI 80
**85960M70**

Single emission recessed downlights for indoor application. The super warm white LED light source with a medium wide flood light distribution is composed of 1 powerled LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 130 lm, with a 86.7 lm/W nominal luminous efficacy.

The device body is made of brass and features a brushed nickel finish, processed by means of brushing.

The ingress protection degree is IP44; the total weight is of 0.037 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 1.5 W The power supply cable is included and features a 0.12 m length.

The device features protection class III and can be wall lights or ceiling-mounted, with a 15 mm diameter hole (in plasterboard) with an outer casing, code 84917(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

| **Energieeffizienzklasse** |
|---|
| Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse F. |

| **Illuminotechnical Eigenschaften** | |
|---|---|
| Lichtstrom (Lichtquelle) | 260 lm |
| Farbtemperatur | 2700 K |
| Standard Deviation of Colour Matching | 1/16 ANSI BIN |
| Farbwiedergabeindex | 80 Ra |
| Standardumgebungstemperatur | -20 / +50°C |
| Typische Temperatur am Glas | 40°C |

| **LED Life / Failure Ratio** |
|---|
| L70 B10 C0 200000h (at Tj 60  Ta 25 ) |
| L80 B10 C0 130000h (at Tj 60  Ta 25 ) |
| L90 B10 C0 60000h (at Tj 60  Ta 25 ) |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Aspho_R | Downlights | Accessories
**85960M70**






Einbaugehäuse

installationsposition: decke; typ installation: mauerwerk L=80mm, H=60mm, D=60mm.

Material:Kunststoff ABS, farbe:Black.

| Code |
| --- |
| 84917 |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.