
Trail_line 3 poles

Systeme | 220-240 V | 120 topLED 42 W DC - 45 W AC
Modular | CRI 80
90925N07





Technische Daten	
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Asymmetric Wallwasher
Light emission direction	downward
Lampe Nennleistung	42 W DC
Gesamtleistung	45 W
Lichtstrom (Lichtquelle)	6186 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	220 - 240 V AC
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	4000 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	1.815 Kg
Modularity	Modular
Schutz vor elektrostatischen Entladungen	Ja
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	Text white RAL9003
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	PMMA

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 220-240 V | 120 topLED 42 W DC - 45 W AC | Modular | CRI 80
90925N07

Single emission systems for indoor application. The natural white LED light source with a asymmetric wallwasher light distribution is composed of 120 topled LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 6186 lm, with a 147.3 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a text white ral9003 finish, processed by means of coating; the diffuser is made of pmma.

The ingress protection degree is IP20; the total weight is of 1.815 kg.

The total absorbed power is 45 W


The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält 2 Lichtquellen der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	93 %
Lichtstrom (Lichtquelle)	6186 lm
Leuchten Lichtstrom	5782 lm
Consumption	45 W
Leuchten Lichtausbeute	128 lm/W
Farbtemperatur	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B20 C0 36000h




Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Trail_line 3 poles

Systeme | 220-240 V | 120 topLED 42 W DC - 45 W AC | Modular | CRI 80
90925N07

Components






Trail Power module backbone 3 poles ON/OFF

Code
90911






Trail Power module backbone 3 poles ON/OFF

Code
90915






Trail standard backbone 3 poles ON/OFF

Code
90903






Trail standard backbone 3 poles ON/OFF - Sistemi

Code
90907






Trail Three-phase adapter

Code
90952






Trail Power Module backbone 7 poles ON/OFF DALI

Code
90913 - 90917






Trail standard backbone 7 poles ON/OFF-DALI

Code
90909 - 90905





Trail Auxiliary power backbone 7 poles ON/OFF

Code
90905E


Systeme | 220-240 V | 120 topLED 42 W DC - 45 W AC | Modular | CRI 80
90925N07

Components

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Trail_line 3 poles | Systems | Accessories
90925N07






Kabel für Aufhängung

Code
90944





Kabel für Aufhängung

Code
90943






Klammer
L=53mm, H=13mm, D=23mm

Code
90945





Endkappe
Material:Aluminium, farbe:weiß RAL 9003, bearbeitungstyp :Lackierung.

Code
90946



Profil
Material:Aluminium, farbe:Text white RAL9003, bearbeitungstyp :Lackierung.

Code
90950

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.