
Birba_S

Deckenleuchten | 220-240 V | 1xGU10
9375







Technische Daten	
Jahr der Verwirklichung	2020
Typ	Deckenleuchten
Installationsposition	Decke
Installationsumgebung	Indoor
Leuchtmittel inbegriffen	Nein
Anschluss der Leuchte	1 x GU10 Max 7W
Light emission direction	downward
Optik	Diffuses
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Nettogewicht	0.225 Kg

Oberfläche Oberfläche Gehäuse	
Material	Messing gebürstet
Farbe	Messing gebürstet

Oberfläche Oberfläche fassung	
Material	Eisen
Farbe	Schwarz RAL 9005
Bearbeitungstyp	Lackierung

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Birba_S

Deckenleuchten | 220-240 V | 1xGU10
9375

Single emission ceiling downlights for indoor application. Compatibility: LED lamp; lamp cap 1xGU10.

The device body is made of brass and features a brass finish; the mounting frame is made of iron, with a black ral 9005 finish, processed by means of coating.

The ingress protection degree is IP20; the total weight is of 0.225 kg.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.