

Systeme | 198-264 V | 288 topLED 54 W DC - 58 W AC | CRI 90
9866







Technische Daten	
Typ	Systeme
Installationsposition	Kabel
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward and upward
Lampe Nennleistung	54 W DC
Gesamtleistung	58 W
Lichtstrom (Lichtquelle)	5652 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	198 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	2
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	1.800 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Aluminium
Farbe	Text black RAL9005
Bearbeitungstyp	Lackierung

Oberfläche Oberfläche diffusor	
Material	PC
Farbe	Opal

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme | 198-264 V | 288 topLED 54 W DC - 58 W AC | CRI 90
9866

Double emission systems for indoor application. The warm white LED light source with a diffused light distribution is composed of 288 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 5652 lm, with a 104.7 lm/W nominal luminous efficacy.


The device body is made of aluminium and features a text black ral9005 finish, processed by means of coating; the diffuser is made of PC.

The ingress protection degree is IP20; the total weight is of 1.800 kg.

The total absorbed power is 58 W

The device features protection class II and can be cable-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Energieeffizienzklasse
Dieses Produkt enthält 6 Lichtquellen der Energieeffizienzklasse F.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	68 %
Lichtstrom (Lichtquelle)	5652 lm
Leuchten Lichtstrom	3885 lm
Consumption	58 W
Leuchten Lichtausbeute	66 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	25°C

LED Life / Failure Ratio
L70 B10 C0 102000h (at Tj 115 Ta 25)
L90 B10 C0 55000h


UGR	
UGR axial	24.1
UGR transversal	28.5
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	180°
Light distribution simmetry	Symmetrical

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.


Systeme | 198-264 V | 288 topLED 54 W DC - 58 W AC | CRI 90
9866

Components


300 System Accessories - Sistemi

Code
TR4101-4


300 System Accessories - Sistemi

Code
TR4101-5

300 System Accessories - Sistemi

Code
TR4103-4


300 System Accessories - Sistemi

Code
TR4103-5





300 System Accessories

Code
TR4104-3


300 System Accessories - 1.5m - Grey - Sistemi

Code
TR4105-5

300 System Accessories

Code
TR4109-4

300 System Accessories

Code
TR4109-5

Systeme | 198-264 V | 288 topLED 54 W DC - 58 W AC | CRI 90
9866

Components

Supporting cable - 50m - Sistemi

Code
TR4151-50

Supporting cable - 30m - Sistemi

Code
TR4151-30

Supporting cable - 20m - Sistemi

Code
TR4151-20



Supporting cable - 10m - Sistemi


Code
TR4151-10



Supporting cable - 5m - Sistemi

Code
TR4151-5






300 System Accessories - 1.5m - White - Sistemi

Code
TR4105-4R






300 System Accessories - Sistemi

Code
8721






300 System Accessories - Sistemi

Code
8722

Systeme | 198-264 V | 288 topLED 54 W DC - 58 W AC | CRI 90
9866

Components






300 System Accessories - Sistemi

Code
8729






300 System Accessories - Sistemi

Code
9873





300 System Accessories

Code
9874



Supporting black cable - 5m

Code
TR4153-5



Supporting black cable - 10m - Sistemi

Code
TR4153-10



Supporting black cable - 20m - Sistemi

Code
TR4153-20



Supporting black cable - 30m - Sistemi

Code
TR4153-30




Supporting black cable - 50m - Sistemi

Code
TR4153-50


Systeme | 198-264 V | 288 topLED 54 W DC - 58 W AC | CRI 90
9866

Components


300 System Accessories - Sistemi

Code
TR4124-4


300 System Accessories - Sistemi

Code
TR4124-5


300 System Accessories - Sistemi

Code
TR4124-6


300 System Accessories - 1.5m - Grey - Sistemi

Code
TR4105-6


300 System Accessories - Sistemi

Code
TR4103-6


300 System Accessories - Sistemi

Code
TR4101-6

300 System Accessories - Sistemi

Code
TR4109-6


300 System Accessories - Sistemi

Code
8730

Systeme | 198-264 V | 288 topLED 54 W DC - 58 W AC | CRI 90
9866

Components





300 System Accessories - Sistemi

Code
8731

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.