
Rubber 3D PROtection

Unterwasserleuchten - LED Strip
112 topLED 75 W DC 24 V | 9.59 W/m | 1059.36 Lm/m | CRI >90
C0012WDI07817







Technische Daten	
Länge	7817 mm
Typ	Oberfläche - LED Strip
Installationsposition	Wand - Decke
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Lampe Nennleistung	75 W DC
Lampenleistung / m	75 W / m
Lichtstrom (Lichtquelle)	8281 lm
Lichtstrom (Lichtquelle) / m	8281 lm / m
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	>90 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP68
Installationsbeschränkung	Nur unter Wasser
IK	IK07
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
ETL	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	10 m
Harzbeschichtung	Ja
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.78 kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Technopolymer
Farbe	Weiß

Oberfläche Oberfläche diffusor	
Material	PU
Farbe	Opal

Elektronik



99331
On/Off Driver 198~264V AC / 176~275V DC 150 W (1 - 2 art.)



99332
1-10V Controller (1 - 2 art.)



99374
On/Off Driver 198~264V AC / 176~275V DC 75 W (1 art.)



83333
Push and Simply Dim - DALI-2 Controller (1 - 2 art.)



C-E400002
Push and Simply Dim - DALI-2 Controller (1 - 3 art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Unterwasserleuchten - LED Strip | 112 topLED 75 W DC 24 V | 9.59 W/m | 1059.36 Lm/m | CRI >90

C0012WDI07817

Single emission submerged or led strip for outdoor application. The warm white LED light source with a diffused light distribution is composed of 112 topled LEDs with CCT of 3000 K and a CRI >90; the source luminous flux is 8281 lm, with a 110.4 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish; the diffuser is made of pu.

The ingress protection degree is IP68; the total weight is of 0.78 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 75 W The power supply cable is included and features a 10 m length.

The device features protection class III and can be wall lights or ceiling-mounted with an outer casing, code C-C300001(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F.


Illuminotechnical Eigenschaften	
Lichtstrom (Lichtquelle)	8281 lm
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	>90 Ra
Standardumgebungstemperatur	-20 / +55°C

LED Life / Failure Ratio
L70 B10 C0 191000h
L80 B10 C0 120000h
L90 B10 C0 58000h

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rubber 3D PROtection | LED Strip | Accessories
C0012WDI07817






Profil - Lineares Weiss Pvc-Profil 19x18x1000mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100002






Profil - Lineares Weiss Pvc-Profil 19x18x2000mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100001






Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x2000mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100004





Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x1000mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100005






Clip - Weißes pvc lineares Profil 19x18x50mm für Rubber 3D PROtection
installationsposition: wand, decke

Code
C-K100003






Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x50mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100006






Einbaugehäuse - Gegengehäuse + Kabelverschraubung Betonbecken
L=300mm, H=36mm, D=36mm.
Material:Kunststoff ABS, farbe:Black.

Code
C-C300001






Lochschablone
Material:Aluminium, farbe:Polished aluminium.

Code
C-V200005

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.


Rubber 3D PROtection | LED Strip | Accessories
C0012WDI07817






Lochschablone - Rubber Vorbereitungsset - Polystyrolstreifen

Code
99521




Zubehör für Außengehäuse

Code
C-K400165



Lochschablone - Rubber Vorbereitungsset - Polystyrolstreifen

Code
C-K400170



Zubehör für Außengehäuse

Code
C-K400171




Kabelklemme

Code
98990



Stecker

Code
89548



Kabelklemme
Material:Kunststoff ABS, farbe:Black.

Code
C-W300001



Strip Service - Doppelseitiges Klebeband 33 Meter

Code
99520

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rubber 3D PROtection | LED Strip | Accessories
C0012WDI07817

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.