
Rubber 3D PROtection

Unterwasserleuchten - LED Strip
topLED 50 W DC 24 V | 10 W/m | 998.4 Lm/m | CRI >90
C00130WHMDI







Technische Daten	
Länge	5000 mm
Minimaler Schnitt	62.5 mm
Typ	Oberfläche - LED Strip
Installationsposition	Wand - Decke
Installationsumgebung	Outdoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	50 W DC
Lampenleistung / m	10 W / m
Lichtstrom (Lichtquelle)	4992 lm
Lichtstrom (Lichtquelle) / m	998.4 lm / m
Ähnlichste Farbtemperatur / Tone	2700 K
Farbwiedergabeindex	>90 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP68
Installationsbeschränkung	Nur unter Wasser
IK	IK07
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
ETL	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	10 m
Harzbeschichtung	Ja
Typ Lichtabstrahlung	Einflammig
Nettogewicht	1.365 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Technopolymer
Farbe	Weiß

Oberfläche Oberfläche diffusor	
Material	PU
Farbe	Opal

Elektronik



99331
On/Off Driver 198~264V AC / 176~275V DC 150 W (1 - 3 art.)



99332
1-10V Controller (1 - 3 art.)



99374
On/Off Driver 198~264V AC / 176~275V DC 75 W (1 art.)



83333
Push and Simply Dim - DALI-2 Controller (1 - 3 art.)



C-E400002
Push and Simply Dim - DALI-2 Controller (1 - 4 art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Unterwasserleuchten - LED Strip | topLED 50 W DC 24 V | 10 W/m | 998.4 Lm/m | CRI >90
C00130WHMDI

Single emission submerged or led strip for outdoor application. The super warm white LED light source with a diffused light distribution is composed of 560 topled LEDs with CCT of 2700 K and a CRI >90; the source luminous flux is 4992 lm, with a 99.8 lm/W nominal luminous efficacy.


The device body is made of technopolymer and features a white finish; the diffuser is made of pu.


The ingress protection degree is IP68; the total weight is of 1.365 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 50 W The power supply cable is included and features a 10 m length.

The device features protection class III and can be wall lights or ceiling-mounted with an outer casing, code C-C300001(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält 5 Lichtquellen der Energieeffizienzklasse F.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	55 %
Lichtstrom (Lichtquelle)	4992 lm
Leuchten Lichtstrom	2760 lm
Consumption	49 W
Leuchten Lichtausbeute	56 lm/W
Farbtemperatur	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	>90 Ra
Standardumgebungstemperatur	-20 / +55°C

LED Life / Failure Ratio
L70 B10 C0 191000h
L80 B10 C0 120000h
L90 B10 C0 58000h


UGR	
UGR axial	20.2
UGR transversal	25.8
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	107°
Optik C0/C180	133°
Light distribution simmetry	Symmetrical 2 assis

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rubber 3D PROtection | LED Strip | Accessories
C00130WHMDI






Profil - Lineares Weiss Pvc-Profil 19x18x2000mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100001





Profil - Lineares Weiss Pvc-Profil 19x18x1000mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100002






Clip - Weißes pvc lineares Profil 19x18x50mm für Rubber 3D PROtection
installationsposition: wand, decke

Code
C-K100003






Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x1000mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100005






Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x2000mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.

Code
C-K100004





Profil - Weißes lineares Profil mit hohlem Durchgang 39x19x50mm für Rubber 3D PROtection
Material:Acrylnitril-Styrol-Acrylat, farbe:weiß RAL 9003.


Code
C-K100006





Einbaugehäuse - Gegengehäuse + Kabelverschraubung Betonbecken
L=300mm, H=36mm, D=36mm.
Material:Kunststoff ABS, farbe:Black.

Code
C-C300001






Lochschablone - Rubber Vorbereitungsset - Polystyrolstreifen

Code
99521

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Rubber 3D PROtection | LED Strip | Accessories
C00130WHMDI






Klammer - Clip mit Kabelkanal
installationsposition: wand, decke L=50mm, H=39mm, D=19mm.
Material:Weiß.

Code
80734






Klammer - Clip
installationsposition: wand, decke L=50mm, H=18mm, D=19mm.
Material:Weiß.

Code
80733





Profil - Lineares Pvc-Profil 19x18x1000mm
Material:Weiß.


Code
80418



Strip Service - Doppelseitiges Klebeband 33 Meter

Code
99520





Lochschablone
Material:Aluminium, farbe:Polished aluminium.

Code
C-V200005

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.