Downlights | 1 arrayLED 26 W DC 750 mA | CRI 90


C00582WHTWF







127



Technische Daten	
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	arrayLED
Optik	Wide Flood
Light emission direction	downward
Lampe Nennleistung	26 W DC
Lichtstrom (Lichtquelle)	4412 lm
Eingangsspannungsbereich	750mA
Ähnlichste Farbtemperatur / Tone	3500 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP20
IP optisches System	IP65
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.3 m
Harzbeschichtung	Nein
Einbautiefe	116 mm
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.77 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Technopolymer
Farbe	Weiß

Oberfläche Oberfläche diffusor	
Material	UV beständiges Polycarbonat
Farbe	Transparent

Oberfläche Oberfläche strahler	
Material	Stranggepresstes Aluminium
Farbe	Aluminium
Bearbeitungstyp	Trommelung

Elektronik



C-E100034
Push and Simply Dim - DALI-2 Controller (- art.)



C-E100033
Multi Power 198~264V AC / V DC (- art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Downlights | 1 arrayLED 26 W DC 750 mA | CRI 90
C00582WHTWF

Single emission recessed downlights for indoor application. The brilliant white LED light source with a wide flood light distribution is composed of 1 arrayled LEDs with CCT of 3500 K and a CRI 90; the source luminous flux is 4412 lm, with a 169.7 lm/W nominal luminous efficacy.


The device body is made of technopolymer and features a white finish; the diffuser is made of uv resistant polycarbonate.


The ingress protection degree is IP20; the total weight is of 0.77 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 26 W The power supply cable is included and features a 0.3 m length.

The device features protection class III and can be ceiling-mounted, with a 127 mm diameter hole (in plasterboard) with an outer casing, code C-C100020(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse D.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	76 %
Lichtstrom (Lichtquelle)	4412 lm
Leuchten Lichtstrom	3382 lm
Consumption	26 W
Leuchten Lichtausbeute	130 lm/W
Farbtemperatur	3500 K
Standard Deviation of Colour Matching	2 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 237564h (at Tj 65 Ta 25)
L70 B10 C0 148736h (at Tj 65 Ta 25)
L90 B10 C0 70385h (at Tj 65 Ta 25)

UGR	
UGR axial	17.2
UGR transversal	17.2
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	51°
Light distribution simmetry	Symmetrical

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Modoc_R | Downlights | Accessories
C00582WHTWF



Optik
Lichtverteilung: spot,Material Verkleidung: uv beständiges polycarbonat

Code
C-K400138



Optik
Lichtverteilung: flood,Material Verkleidung: uv beständiges polycarbonat

Code
C-K400139



Optik
Lichtverteilung: medium wide flood,Material Verkleidung: uv beständiges polycarbonat

Code
C-K400140



Optik
Lichtverteilung: wide flood,Material Verkleidung: uv beständiges polycarbonat

Code
C-K400141



Werkzeug - Saugnapf zum Herausziehen der Optik
Material:, farbe:Transparent.


Code
C-F600002



Diffusor
Diffusorart: filtro ellittico

Code
C-U300021






Diffusor
Diffusorart: transparent closing screen.
Material:PC, farbe:Transparent.

Code
C-U300039






Diffusor - Achtung: Um das Zubehör zu verwenden, muss die an der Lampe angebrachte Optik entfernt werden
Diffusorart: diffused closing screen.
Material:PC, farbe:Opal.

Code
C-U300040

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.


Modoc_R | Downlights | Accessories
C00582WHTWF






Einbaugehäuse
installationsposition: decke; typ installation: mauerwerk L=382mm, H=142mm, D=342mm.
Material:Polypropylen, farbe:Weiß.

Code
C-C100016





Einbaugehäuse
installationsposition: decke; typ installation: mauerwerk L=687mm, H=142mm, D=382mm.
Material:Polypropylen, farbe:Weiß.

Code
C-C100017



Einbaugehäuse - Gitter für Außengehäuse
installationsposition: decke; typ installation: mauerwerk L=210mm, H=210mm, D=10mm.
Material:Polypropylen, farbe:Weiß.

Code
C-C100020

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.