
| CRI 90
C0060MDI05019







Technische Daten	
Jahr der Verwirklichung	2020
Typ	Lineare Elemente
Installationsposition	Kabel
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	63 W DC
Lichtstrom (Lichtquelle)	7166 lm
Frequency	50-60 Hz
Ähnlichste Farbtemperatur / Tone	2700 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	CV
Isolierklasse	3
IP	IP40
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V - PUSH DIM
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Ja
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.520 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	PU
Farbe	Weiß

Oberfläche Oberfläche fassung	
Material	PC
Farbe	Schwarz RAL 9005
Bearbeitungstyp	Lackierung

Elektronik



81416
On/Off Driver 220~240V AC 120 W (1 art.)



83041
1-10V - Push and Simply Dim - DALI-2 Controller (- art.)



81417
On/Off Driver 220~240V AC 180 W (1 - 2 art.)



83042
1-10V - Push and Simply Dim - DALI-2 Controller (- art.)



83415
On/Off Driver 220~240V AC 120 W (- art.)



83416
On/Off Driver 220~240V AC 180 W (- art.)



83429
On/Off Driver 220~240V AC 120 W (- art.)



83431
On/Off Driver 220~240V AC 180 W (- art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

| CRI 90
C0060MDI05019

Single emission systems or lines for indoor application. The super warm white LED light source with a diffused light distribution is composed of 350 topled LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 7166 lm, with a 113.7 lm/W nominal luminous efficacy.

The device body is made of pu and features a white finish; the mounting frame is made of PC, with a black ral 9005 finish, processed by means of coating.

The ingress protection degree is IP40; the total weight is of 0.520 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 63 W

The device features protection class III and can be cable-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.


Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse G.


Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	75 %
Lichtstrom (Lichtquelle)	7166 lm
Leuchten Lichtstrom	5405 lm
Consumption	63 W
Leuchten Lichtausbeute	85 lm/W
Farbtemperatur	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
Standardumgebungstemperatur	-20 / +50°C

LED Life / Failure Ratio
L70 B20 C0 102000h (at Tj 115 Ta 25)
L90 B10 C0 55000h

UGR	
UGR axial	28.7
UGR transversal	28.6
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C90/C270	115°
Optik C0/C180	120°
Light distribution simmetry	Symmetrical 2 assis






Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.


Ink system_L | Lines | Accessories
C0060MDI05019






Drahtabdeckung - Abzweigdose schwarz
Material:PC, bearbeitungstyp :Lackierung.


Code
81424





Kabelverbindung
Typ linear.
Material:PC, bearbeitungstyp :Lackierung.


Code
81418





Kabelverbindung - L-Verbindungsstück schwarz, elektrifiziert
Typ linear.
Material:PC, bearbeitungstyp :Lackierung.


Code
81419





Kabelverbindung
Typ linear.
Material:PC, bearbeitungstyp :Lackierung.

Code
81420






Endkappe - Verschlusskappe schwarz, elektrifiziert
Material:PC, bearbeitungstyp :Lackierung.

Code
81421






Profil
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
84010





Profil
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
84011






Klammer - 2X
installationsposition: wand, decke.
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
84017

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L | Lines | Accessories
C0060MDI05019






Drahtabdeckung - 2X
Material:Eisen, bearbeitungstyp :Lackierung.

Code
81422






Drahtabdeckung - 2X
Material:PC, bearbeitungstyp :Lackierung.

Code
81423






Kabel für Aufhängung
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
81425





Lochschablone
Material:Eisen, bearbeitungstyp :Lackierung.

Code
83186






Werkzeug - Set zum Schneiden/Abisolieren von Kabeln
Material:Stahl, farbe:Stahl.

Code
81427





Kabel für Aufhängung
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
83426

Schiene
Länge: 1000mm.
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
83432

Schiene
Länge: 2000mm.
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
83434

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L | Lines | Accessories
C0060MDI05019

	Kabelverbindung Material:Aluminium, bearbeitungstyp :Lackierung.	**Code** 83436
	Kabelverbindung Material:Aluminium, bearbeitungstyp :Lackierung.	**Code** 83438
	Kabelverbindung Material:Aluminium, bearbeitungstyp :Lackierung.	**Code** 83440
	Kabelverbindung	**Code** 83442
	Kabel für Aufhängung Material:Aluminium, bearbeitungstyp :Lackierung.	**Code** 83443
	Kabel Länge 1000 mm; farben: schwarz.	**Code** 83445
	Kabel Länge 1000 mm; farben: schwarz.	**Code** 83446
 	Profil - Kit 2 x Material:Aluminium, bearbeitungstyp :Lackierung.	**Code** 81430

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Ink system_L | Lines | Accessories
C0060MDI05019





Profil - Kit 5 x
Material:Aluminium, bearbeitungstyp :Lackierung.

Code
81426



Kabel
Typ Kabel power cable; Länge 5000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: weiß - rot.

Code
83412



Kabel
Typ Kabel power cable; Länge 10000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: weiß - rot.

Code
83413



Kabel
Typ Kabel power cable; Länge 1000 mm; isolierung doppio; querschnitt 1.5 mm²; kabelklemme: nein; farben: schwarz - rot.

Code
83414

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.