
Downlights | 1 arrayLED 10 W DC 300 mA | CRI 80

C00693WHAFL







Technische Daten	
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	arrayLED
Optik	Flood
Light emission direction	downward
Lampe Nennleistung	10 W DC
Lichtstrom (Lichtquelle)	1570 lm
Eingangsspannungsbereich	300mA
Ähnlichste Farbtemperatur / Tone	2200 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP20
IP optisches System	IP65
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.3 m
Harzbeschichtung	Nein
Einbautiefe	81 mm
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.212 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Technopolymer
Farbe	Weiß

Oberfläche Oberfläche diffusor	
Material	UV beständiges Polycarbonat
Farbe	Transparent

Oberfläche Oberfläche strahler	
Material	Stranggepresstes Aluminium
Farbe	Aluminium
Bearbeitungstyp	Trommelung

Elektronik



99734
Multi Power 198~264V AC / 180~275V DC (1 art.)



99732
1-10V Multi Power 198~264V AC / V DC (1 art.)



83322
Push and Simply Dim - DALI-2 Controller (1 art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Downlights | 1 arrayLED 10 W DC 300 mA | CRI 80
C00693WHAFL

Single emission recessed downlights for indoor application. The ancient white LED light source with a flood light distribution is composed of 1 arrayled LEDs with CCT of 2200 K and a CRI 80; the source luminous flux is 1570 lm, with a 157.0 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP20; the total weight is of 0.212 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 10 W The power supply cable is included and features a 0.3 m length.

The device features protection class III and can be ceiling-mounted with an outer casing, code C-C100008(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.


Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E.


Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	77 %
Lichtstrom (Lichtquelle)	1570 lm
Leuchten Lichtstrom	1212 lm
Consumption	10 W
Leuchten Lichtausbeute	121 lm/W
Farbtemperatur	2200 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 237566h (at Tj 65 Ta 25)
L80 B10 C0 148737h (at Tj 65 Ta 25)
L90 B10 C0 70385h (at Tj 65 Ta 25)

UGR	
UGR transversal	8.4
UGR axial	8.4
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	29°
Light distribution simmetry	Symmetrical





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Modoc_RF | Downlights | Accessories
C00693WHAFL



Optik
Lichtverteilung: spot,Material Verkleidung: uv beständiges polycarbonat

Code
83382



Optik
Lichtverteilung: flood,Material Verkleidung: uv beständiges polycarbonat

Code
83383



Optik
Lichtverteilung: medium wide flood,Material Verkleidung: uv beständiges polycarbonat

Code
C-K400132



Optik
Lichtverteilung: wide flood,Material Verkleidung: uv beständiges polycarbonat

Code
83384



Werkzeug - Saugnapf zum Herausziehen der Optik
Material:, farbe:Transparent.

Code
C-F600002



Einbaugehäuse
installationsposition: decke; typ installation: gipskarton L=92mm, H=40mm, D=92mm.
Material:PC, farbe:Transparent.

Code
C-C100008



Diffusor
Diffusorart: filtro ellittico

Code
C-U300019




Diffusor
Diffusorart: transparent closing screen.
Material:PC, farbe:Transparent.

Code
C-U300035

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Modoc_RF | Downlights | Accessories
C00693WHAFL





Diffusor - Achtung: Um das Zubehör zu verwenden, muss die an der Lampe angebrachte Optik entfernt werden
Diffusorart: diffused closing screen.
Material:PC, farbe:Opal.

Code
C-U300036

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.