
Downlights | 1 arrayLED 37 W DC 1100 mA | CRI 80

C00696WHASP







Technische Daten	
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	arrayLED
Optik	Spot
Light emission direction	downward
Lampe Nennleistung	37 W DC
Lichtstrom (Lichtquelle)	5670 lm
Eingangsspannungsbereich	1100mA
Ähnlichste Farbtemperatur / Tone	2200 K
Farbwiedergabeindex	80 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP20
IP optisches System	IP65
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	0.3 m
Harzbeschichtung	Nein
Einbautiefe	121 mm
Typ Lichtabstrahlung	Einflammig
Nettogewicht	1.189 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Technopolymer
Farbe	Weiß

Oberfläche Oberfläche diffusor	
Material	UV beständiges Polycarbonat
Farbe	Transparent

Oberfläche Oberfläche strahler	
Material	Stranggepresstes Aluminium
Farbe	Aluminium
Bearbeitungstyp	Trommelung

Elektronik



83008
1-10V - Push and Simply Dim - DALI-2 Controller



C-E100048
NFC Multi Power 198~264V AC / V DC

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Downlights | 1 arrayLED 37 W DC 1100 mA | CRI 80
C00696WHASP

Single emission recessed downlights for indoor application. The ancient white LED light source with a spot light distribution is composed of 1 arrayled LEDs with CCT of 2200 K and a CRI 80; the source luminous flux is 5670 lm, with a 153.2 lm/W nominal luminous efficacy.

The device body is made of technopolymer and features a white finish; the diffuser is made of uv resistant polycarbonate.

The ingress protection degree is IP20; the total weight is of 1.189 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 37 W The power supply cable is included and features a 0.3 m length.

The device features protection class III and can be ceiling-mounted with an outer casing, code C-C100012(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.


Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E.


Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	76 %
Lichtstrom (Lichtquelle)	5670 lm
Leuchten Lichtstrom	4322 lm
Consumption	37 W
Leuchten Lichtausbeute	116 lm/W
Farbtemperatur	2200 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	80 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 213405h (at Tj 65 Ta 25)
L80 B10 C0 133623h (at Tj 65 Ta 25)
L90 B10 C0 63251h (at Tj 65 Ta 25)

UGR	
UGR transversal	10.7
UGR axial	10.7
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Optik C0/C180	19°
Light distribution simmetry	Symmetrical





Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Modoc_RF | Downlights | Accessories
C00696WHASP



Optik
Lichtverteilung: spot,Material Verkleidung: uv beständiges polycarbonat

Code
C-K400144



Optik
Lichtverteilung: flood,Material Verkleidung: uv beständiges polycarbonat

Code
C-K400145



Optik
Lichtverteilung: medium flood,Material Verkleidung: uv beständiges polycarbonat

Code
C-K400146



Optik
Lichtverteilung: wide flood,Material Verkleidung: uv beständiges polycarbonat


Code
C-K400147



Werkzeug - Saugnapf zum Herausziehen der Optik
Material:, farbe:Transparent.

Code
C-F600002






Diffusor
Diffusorart: transparent closing screen.
Material:PC, farbe:Transparent.

Code
C-U300041





Diffusor - Achtung: Um das Zubehör zu verwenden, muss die an der Lampe angebrachte Optik entfernt werden
Diffusorart: diffused closing screen.
Material:PC, farbe:Opal.

Code
C-U300042




Diffusor
Diffusorart: filtro ellittico

Code
C-U300022

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Modoc_RF | Downlights | Accessories
C00696WHASP





Einbaugehäuse
installationsposition: decke; typ installation: gipskarton L=200mm, H=40mm, D=200mm.
Material:PC, farbe:Transparent.

Code
C-C100012

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.