
Creek Optus

Systeme - Scheinwerfer
1 x powerLEDs 8.5 W DC 700 mA | CRI 90
C01133WHWUS







Technische Daten	
Typ	Kanäle - Scheinwerfer
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	powerLEDs
Optik	Ultra Spot
Light emission direction	frontal
Lampe Nennleistung	8.5 W DC
Lichtstrom (Lichtquelle)	731 lm
Eingangsspannungsbereich	700mA
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	CC
Isolierklasse	3
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Nein
Leuchte dimmbar	DALI - 1-10V
Schwenkbarkeit	Estraibile
Gesamtwinkel (vertikale Ebene)	180 °
Gesamtwinkel (horizontale Ebene)	355 °
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Nettogewicht	0.6 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Stranggepresstes Aluminium EN AB - 46100
Farbe	Text white RAL9003
Bearbeitungstyp	Pulverbeschichtung mit duroplastischen Pulvern

Oberfläche Oberfläche sockel	
Material	Eisen
Farbe	Zink

Elektronik



99147
On/Off Driver 198~264V AC (- art.)



83008
1-10V - Push and Simply Dim - DALI-2 Controller (1 - 2 art.)



C-E100016
Push and Simply Dim - DALI-2 Controller (1 - 3 art.)

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Systeme - Scheinwerfer | 1 x powerLEDs 8.5 W DC 700 mA | CRI 90
C01133WHWUS

Single emission systems or projectors for indoor application. The warm white LED light source with a ultra spot light distribution is composed of 1 powerled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 731 lm, with a 86.0 lm/W nominal luminous efficacy.

The device body is made of die-cast aluminium en ab - 46100 and features a text white ral9003 finish, processed by means of powder coating with thermosetting powders.

The ingress protection degree is IP20; the total weight is of 0.6 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 8.5 W

The device features protection class III and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.


Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F.


Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	75 %
Lichtstrom (Lichtquelle)	731 lm
Leuchten Lichtstrom	551 lm
Consumption	8.5 W
Leuchten Lichtausbeute	64 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Standardumgebungstemperatur	-20 / +50°C
Typische Temperatur am Glas	40°C

LED Life / Failure Ratio
L70 B10 C0 716641h (at Tj 65 Ta 25)
L80 B10 C0 445035h (at Tj 65 Ta 25)
L90 B10 C0 205461h (at Tj 65 Ta 25)

UGR	
UGR axial	14.4
UGR transversal	14.4
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20


OPTICAL	
Optik C0/C180	6°
Light distribution simmetry	Symmetrical






Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.


Creek Optus | Projectors | Accessories
C01133WHWUS






Fuhrmann - Lineargehäuse (Paar)
installationsposition: decke L=500mm, H=39.5mm, D=418mm.
Material:Polystyrol, farbe:Weiß matt.


Code
82728






Fuhrmann - Lineargehäuse (Paar)
installationsposition: decke L=1000mm, H=39.5mm, D=418mm.
Material:Polystyrol, farbe:Weiß matt.

Code
82729






Fuhrmann - Lineargehäuse (Paar)
installationsposition: decke L=1500mm, H=39.5mm, D=418mm.
Material:Polystyrol, farbe:Weiß matt.

Code
82730






Fuhrmann - Obere Abdeckung carter
installationsposition: decke L=500mm, H=161mm, D=425mm.
Material:Eisen, farbe:Schwarz RAL 9005, bearbeitungstyp :Lackierung.

Code
99927






Fuhrmann - Obere Abdeckung carter
installationsposition: decke L=1000mm, H=161mm, D=425mm.
Material:Eisen, farbe:Schwarz RAL 9005, bearbeitungstyp :Lackierung.

Code
99928





Fuhrmann - Verschlusskappe
installationsposition: decke L=425mm, H=168mm, D=26mm.
Material:Eisen, farbe:Matt black (R9005), bearbeitungstyp :Pulverbeschichtung mit duroplastischen Pulvern.

Code
99929

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.