
# Puccini_P

Pendelleuchte | 1 arrayLED 4 W DC - 5 W AC
CRI 90
**CA141ACHMDI**








| Technische Daten | |
|---|---|
| Typ | Pendelleuchte |
| Installationsposition | Decke |
| Installationsumgebung | Indoor |
| Lichtquelle | LED |
| Circuit structure | arrayLED |
| Optik | Diffuses |
| Light emission direction | downward |
| Lampe Nennleistung | 4 W DC |
| Gesamtleistung | 5 W |
| Lichtstrom (Lichtquelle) | 435 lm |
| Nominale Eingangsspannung | 220 - 240 V AC |
| Ähnlichste Farbtemperatur / Tone | 3000 K |
| Farbwiedergabeindex | 90 Ra |
| Gleichstrom/Gleichspannung | AC |
| Isolierklasse | 1 |
| IP | IP20 |
| Glühdrahtprüfung | 650° |
| Direkte Montage auf normal entflammbaren Oberflächen | Ja |
| CE | Ja |
| Einschließlich Driver | Driver |
| Leuchte dimmbar | Nein |
| Schwenkbarkeit | Nein |
| Drehbarkeit | Nein |
| Begehbarkeit | Nein |
| Überrollbarkeit | Nein |
| Einschließlich Kabel | Ja |
| Kabellänge | 3 m |
| Harzbeschichtung | Nein |
| Typ Lichtabstrahlung | Einflammig |
| Nettogewicht | 0.545 Kg |
| Schutz vor elektrostatischen Entladungen | Ja |
| Schutz vor Stoßspannungen | Ja |

| Oberfläche Oberfläche Gehäuse | |
|---|---|
| Material | Aluminium |
| Farbe | Polished (galvanic) chrome |
| Bearbeitungstyp | Tampongalvanisieren |

| Oberfläche Oberfläche diffusor | |
|---|---|
| Material | PMMA |
| Farbe | Transparent |

| Oberfläche Oberfläche fassung | |
|---|---|
| Material | Aluminium |
| Farbe | Polished (galvanic) chrome |
| Bearbeitungstyp | Tampongalvanisieren |

| Cables Electrification+suspension | |
|---|---|
| Max. Kabellänge | 3000 mm |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Pendelleuchte | 1 arrayLED 4 W DC - 5 W AC | CRI 90
**CA141ACHMDI**

Single emission pendant luminaires for indoor application. The super warm white LED light source with a diffused light distribution is composed of 1 arrayled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 435 lm, with a 108.8 lm/W nominal luminous efficacy.


The device body is made of aluminium and features a polished (galvanic) chrome finish, processed by means of electroplating; the diffuser is made of pmma; the mounting frame is made of aluminium, with a polished (galvanic) chrome finish, processed by means of electroplating.


The ingress protection degree is IP20; the total weight is of 0.545 kg.

The total absorbed power is 5 W The power supply cable is included and features a 3 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.




| Energieeffizienzklasse |
|---|
| Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F. |

| Illuminotechnical Eigenschaften | |
|---|---|
| Light Output Ratio (LOR) | 73 % |
| Lichtstrom (Lichtquelle) | 435 lm |
| Leuchten Lichtstrom | 320 lm |
| Consumption | 5 W |
| Leuchten Lichtausbeute | 64 lm/W |
| Farbtemperatur | 3000 K |
| Standard Deviation of Colour Matching | 2 Step MacAdam |
| Farbwiedergabeindex | 90 Ra |
| Verbindungstemperatur (Leuchte) | 80 |
| Standardumgebungstemperatur | 25°C |

| LED Life / Failure Ratio |
|---|
| L70 B10 C0 90000h |
| L90 B10 C0 92971h |

| UGR | |
|---|---|
| UGR transversal | 24.8 |
| UGR axial | 25.1 |
| X=4H \| Y=8H | S=0.25H |
| Reflection factor | 70/50/20 |

| OPTICAL | |
|---|---|
| Optik C0/C180 | 31° |
| Light distribution simmetry | Symmetrical |



Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.