
STILNOVO

Mongolfier

Pendelleuchte | 198-264 V
1 topLED 29 W DC - 35 W AC | CRI 90
CZ032DBCMDI







Technische Daten	
Designer	Stilnovo
Jahr der Verwirklichung	2016
Typ	Pendelleuchte
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Circuit structure	topLED
Optik	Diffuses
Light emission direction	downward
Lampe Nennleistung	29 W DC
Gesamtleistung	35 W
Lichtstrom (Lichtquelle)	2436 lm
Nominale Eingangsspannung	220 - 240 V AC
Eingangsspannungsbereich	198 - 264 V AC
Frequency	50 - 60 Hz
Ähnlichste Farbtemperatur / Tone	2700 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammbaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Phase cut
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	3 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Einflammig
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein

Oberfläche Oberfläche Gehäuse	
Material	Metall
Bearbeitungstyp	Tampongalvanisieren

Oberfläche Oberfläche diffusor	
Material	PMMA
Bearbeitungstyp	Satinieren

Oberfläche Oberfläche fassung	
Material	Metall
Bearbeitungstyp	Tampongalvanisieren

Cables Electrification+suspension	
Max. Kabellänge	3000 mm

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Pendelleuchte | 198-264 V | 1 topLED 29 W DC - 35 W AC | CRI 90
CZ032DBCMDI

Single emission pendant luminaires for indoor application. The super warm white LED light source with a diffused light distribution is composed of 1 topled LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 2436 lm, with a 84.0 lm/W nominal luminous efficacy.


The device body is made of metal, processed by means of electroplating; the diffuser is made of pmma with a satin finishing treatment; the mounting frame is made of metal, processed by means of electroplating.


The ingress protection degree is IP20;

The total absorbed power is 35 W The power supply cable is included and features a 3 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energieeffizienzklasse
Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	79 %
Lichtstrom (Lichtquelle)	2436 lm
Leuchten Lichtstrom	1943 lm
Consumption	35 W
Leuchten Lichtausbeute	55 lm/W
Farbtemperatur	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra

LED Life / Failure Ratio
L70 B10 C0 181000h (at Tj 105 Ta 25)
L80 B10 C0 159700h
L90 B10 C0 74560h

UGR	
UGR axial	15.8
UGR transversal	16
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20


OPTICAL	
Optik C0/C180	99°
Light distribution simmetry	Symmetrical

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Mongolfier | Pendant Luminaires | Accessories

CZ032DBCMDI






Dimmer - Phasenabschnitt, CASAMBI - Unverzichtbar zum Dimmen der Lampe mit Casambi Radio-frequenza, 85-240V

Code

KIT0080





Dimmer - Phasenabschnitt (max. 100 W) – wichtig zum Dimmen der Lampe 220-240V

Code

KIT0026

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.