
8LT7GLE4


BLINKING LIGHT MODULE. Ø70MM. BA15D FITTING, RED, 110...120VAC



General characteristics			
Diameter		mm - inch	70 / 2.75
Supply voltage (AC)		V	110…120
Colour			Red
IEC degree of protection			IP65
Mechanical features			
Weight		g	83
Ambient conditions			
Temperature			
	Operating temperature		
	min	°C	-20
	max	°C	+50

Dimensions






Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

8LT7GLE4

BLINKING LIGHT MODULE. Ø70MM. BA15D FITTING, RED, 110...120VAC



Connect terminals C and 1 as indicated to power the first module.
If other modules are fitted, the respective terminals must be connected accordingly.

Certifications and compliance

Compliance	
	CSA C22.2 n° 14
	IEC/EN 60947-1
	IEC/EN 60947-5-1
	UL508
Certificates	
	cULus
	EAC

ETIM classification

ETIM 8.0	EC000232 - Optical module for signal tower

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding