8LT7GLE6

MODUŁ ŚWIATŁA PULSUJĄCEGO, Ø70MM, NIEBIESKI, 115VAC, BEZ ŻARÓWKI



Charakterystyka ogólna

Średnica		mm - inch	70 / 2.75
Napięcie zasilania (AC)		V	110…120
Kolor			Niebieski
Stopień ochrony według IEC			IP65

Właściwości mechaniczne

Masa		g	83


Warunki otoczenia


Temperatura

Temperatura pracy

min.	°C	-20
maks.	°C	+50


Wymiary





Schemat połączeń elektrycznych

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding



Connect terminals C and 1 as indicated to power the first module.
If other modules are fitted, the respective terminals must be connected accordingly.

Certyfikaty i zgodność

Zgodność	
	CSA C22.2 n° 14
	IEC/EN 60947-1
	IEC/EN 60947-5-1
	UL508
Certyfikaty	
	cULus
	EAC

Klasyfikacja ETIM

ETIM 8,0	EC000232 - Moduł świetlny dla kolumny sygnalizacyjnej

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding