
8LT7GLM5


MODUŁ ŚWIATŁA PULSUJĄCEGO, Ø70MM, ŻÓŁTY, 240VAC, BEZ ŻARÓWKI



Charakterystyka ogólna			
Średnica		mm - inch	70 / 2.75
Napięcie zasilania (AC)		V	230…240
Kolor			Żółty
Stopień ochrony według IEC			IP65
Właściwości mechaniczne			
Masa		g	83
Warunki otoczenia			
Temperatura			
Temperatura pracy			
	min.	°C	-20
	maks.	°C	+50

Wymiary






Schemat połączeń elektrycznych

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

8LT7GLM5

MODUŁ ŚWIATŁA PULSUJĄCEGO, Ø70MM, ŻÓŁTY, 240VAC, BEZ ŻARÓWKI



Connect terminals C and 1 as indicated to power the first module.
If other modules are fitted, the respective terminals must be connected accordingly.

Certyfikaty i zgodność

Zgodność

CSA C22.2 n° 14
IEC/EN 60947-1
IEC/EN 60947-5-1
UL508

Certyfikaty

cULus
EAC

Klasyfikacja ETIM

ETIM 8,0

EC000232 - Moduł świetlny dla kolumny sygnalizacyjnej

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding