GX2055U47

ŁĄCZNIK KRZYWKOWY SERII GX, PRZEŁĄCZNIK SIECI BEZ 0, 2 POLA, 20A, DO MONTAŻU TABLICOWEGO W OTWORZE 22MM Z CZARNYM POKRĘTŁEM, MONTOWANYM NA ZATRZASK DO KORPUSU I TABLICZKĄ 48X48MM

Charakterystyka ogólna

Schemat przełączenia			55 - Przełącznik, bez 0, 2 polowy
N° of elements			2
Rodzaj montażu			U47 - wersja do montażu zatrzaskowego w otworze o średnicy 22mm z czarnym pokrętłem

Właściwości styków

Znamionowe napięcie izolacji Ui			
	IEC/EN	V	690
	UL/CSA	V	600
Znamionowe napięcie udarowe Uimp		kV	6
Prąd cieplny umowny Ith			
	IEC/EN	A	20
	UL/CSA	A	15
Znamionowe napięcie robocze		V	440
Znamionowe napięcie udarowe		kV	4
Maksymalna wartość bezpiecznika (gG) do ochrony zwarciowej In			
	10 kA	A	20
	15 kA	A	20
	25 kA	A	20
Prąd udarowy wytrzymywany Icw			
	1 s	kA	250
Przewodność			10/5 mA/V
Prąd roboczy Ie IEC/EN			
AC1/AC21A			
		A	20
AC15			
	110 V	A	10
	220/230 V	A	8
	380/400 V	A	6
	660/690 V	A	1.5
Znamionowa moc robocza w AC			
Trójfazowy AC-3			
	220/230 V	kW	3.7
	380/440 V	kW	5.5
	500/690 V	kW	5.5
Jednofazowy AC-3			
	110 V	kW	0.75
	220/230 V	kW	1.8
	380/440 V	kW	3
Trójfazowy AC23A			
	220/230 V	kW	4
	380/440 V	kW	7.5
	500/690 V	kW	7.5
Jednofazowy AC23A			
	110 V	kW	0.75
	220/230 V	kW	2.2
	380/440 V	kW	3.5
Znamionowy prąd roboczy w DC			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

	DC21A			
		48 V	A	20
		60 V	A	20
		110 V	A	4
		220 V	A	0.6
		440 V	A	0.25
	DC23A (pola szeregowo)			
		24 V	A	20 (1)
		48 V	A	20 (2)
		60 V	A	20 (3)
		110 V	A	10 (3)
		220 V	A	8 (4)
	DC13			
		24 V	A	20
		48 V	A	16
		60 V	A	12
		110 V	A	1
		220 V	A	0.4
		440 V	A	0.15
Rozproszenie mocy			W	0.6
Właściwości mechaniczne				
Zacisk śrubowy				M3
Moment obrotowy dokręcania zacisków maks.			Nm	0.8
Rozmiar przewodu				
	AWG - Przewód sztywny			
		min.	AWG	20
		maks.	AWG	12
	AWG - Przewód elastyczny			
		min.	AWG	20
		maks.	AWG	12
	Przekrój przewodu (IEC) - Przewód elastyczny			
		min.	mm²	0.5
		maks.	mm²	2.5
	Przekrój przewodu (IEC) - Przewód sztywny			
		min.	mm²	0.5
		maks.	mm²	2.5
Trwałość mechaniczna			cycles	1X10⁶
Dane techniczne UL				
Sterowanie bezpośrednie silnika (UL/CSA-DOL)				
	dla trójfazowego silnika			
		120 V	HP	1.5
		240 V	HP	3
		480 V	HP	5
		600 V	HP	5
	dla jednofazowego silnika			
		120 V	HP	0.75
		240 V	HP	1.5
Warunki otoczenia				
Temperatura				
	Temperatura pracy			
		min.	°C	-25
		maks.	°C	+55
	Temperatura składowania			
		min.	°C	-40


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

	maks.	°C	+70

Odporność i zabezpieczenie


Stopień ochrony IP od frontu	IP65
Stopień ochrony IP zacisków	IP20

Wymiary



Series	Dimensions		L			
	□A	E	1	2	3.....8	
GX16	48	26.5	64.9	73.4	81.9	124.4
GX20	48	26.5	64.9	73.4	81.9	124.4

Schemat połączeń elektrycznych



Certyfikaty i zgodność

Zgodność

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-3
IEC/EN/BS 60947-5-1
IEC/EN/BS 61058-1
UL60947-4-1

Certyfikaty

cULus
EAC

Klasyfikacja ETIM

ETIM 8,0	EC001029 - Przełącznik, kompletny

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding