KEN1M1120F

SAFETY SWITCH WITH SOLENOID. KEY CONTACTS 1NC. SOLENOID CONTACTS 2NC+1NO. SOLENOID SUPPLY 120VAC/DC




General characteristics				
General characteristics				
Housing Material				Polymer thermoplastic
Contact characteristics				
Type of contact				1NC (Key), 2NC+1NO (Solenoid)
Thermal current Ith			A	10
IEC/EN 60947-5-1 designation				A300 Q300
Rated insulation voltage Ui			V	250
Rated impulse withstand voltage Uimp			kV	2.5
Short-circuit protection with fuse			Class/A	10 gG
IEC Conventional free air thermal current Ith ≤ 40°C			A	10
Operations				
Mechanical life			cycles	1000000
B10d			cycles	4000000
Mechanical operation			cycles/h	600
Output characteristics				
Mechanical life			cycles	1000000
Mechanical features				
Operating head fixing				Screwed
Operating torque			N	15 (actuator insertion), 30 (Release actuator extraction), 1200 (locked actuator holding)
Tightening torque (Max)				
	Switch fixing		Nm	2.5
	Contact terminals		Nm	0.8
	Body lid screw fixing		Nm	0.8
Conductor section				
	IEC			
		min	mm²	1 or 2
		max	mm²	1.5
Cable connection				Self-releasing screw terminal
Cable entry				3 x M20
Weight			g	440
Ambient conditions				
Pollution degree				3

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Temperature

Operating temperature			
	max	°C	+55
Storage temperature			
	min	°C	-40
	max	°C	+70

Dimensions




Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

KEN1M1120F

SAFETY SWITCH WITH SOLENOID. KEY CONTACTS 1NC. SOLENOID CONTACTS 2NC+1NO. SOLENOID SUPPLY 120VAC/DC



Certifications and compliance

Compliance

CSA C22.2 n°14
IEC/EN 60204
IEC/EN 60947-1
IEC/EN 60947-5-1
UL508
UNI EN ISO 14119

Certificates

cULus
EAC

ETIM classification

ETIM 8.0	EC000030 - End switch

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding