# LPCBL106K11PB6

ZESTAW: PRZYCISK PLASTIKOWY PODŚWIETLANY, SAMOCZYNNY POWRÓT, KRYTY, NIEBIESKI. ADAPTER MONTAŻOWY. ZESTYKI 1NO+1NC, ZACISKI ŚRUBOWE. LAMPKA LED, ŚWIATŁO CIĄGŁE, ZASILANIE 12...30VAC/DC.



| | | | |
|---|---|---|---|
| **Charakterystyka ogólna** | | | |
| Kolor | | | Niebieski |
| Typ pozycji | | | Przycisk kryty |
| Stopień ochrony według IEC | | | IP66, IP67 oraz IP69K |
| **Właściwości elektryczne** | | | |
| Znamionowe napięcie izolacji Ui IEC/EN | | V | 690 |
| Prąd roboczy termiczny umowny Ith, IEC ≤ 40°C | | A | 10 |
| Napięcie zasilania (AC) | | V | 12…30 |
| Napięcie zasilania (DC) | | V | 12…30 |
| Przewodność | | | 1mA 5V |
| Oznaczenie UL/CSA i PN-EN 60947-5-1 | | | A600 Q600 |
| Prąd roboczy AC15 | | | |
| | 12 V | A | 6 |
| | 24 V | A | 6 |
| | 48 V | A | 6 |
| | 120 V | A | 6 |
| | 240 V | A | 3 |
| | 400 V | A | 1.9 |
| | 480 V | A | 1.5 |
| | 500 V | A | 1.4 |
| | 600 V | A | 1.2 |
| Prąd roboczy DC13 | | | |
| | 12 V | A | 3 |
| | 24 V | A | 3 |
| | 48 V | A | 1.5 |
| | 125 V | A | 0.55 |
| | 250 V | A | 0.27 |
| | 440 V | A | 0.15 |
| | 500 V | A | 0.13 |
| | 600 V | A | 0.1 |
| Rezystancja zestyków | | mΩ | ≤20 |
| **Trwałość** | | | |
| elektryczna | | hours | 100000 |
| **Właściwości mechaniczne** | | | |
| Siła zadziałania | | kg-lb | <0.5Kg / 1.1lb |
| Zacisk śrubowy | | | Śruba |
| Przekrój przewodu | | | |
| IEC | | | |
| | maks. | mm² | 1 or 2 / 2.5 |
| Adapter do montażu | | | LPXAU120 |
| **Dane techniczne UL** | | | |
| Stopień ochrony według UL | | | Typ 1, 2, 3R, 4, 4X, 12, 12K |
| **Warunki otoczenia** | | | |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

# LPCBL106K11PB6

ZESTAW: PRZYCISK PLASTIKOWY PODŚWIETLANY, SAMOCZYNNY POWRÓT, KRYTY, NIEBIESKI. ADAPTER MONTAŻOWY. ZESTYKI 1NO+1NC, ZACISKI ŚRUBOWE. LAMPKA LED, ŚWIATŁO CIĄGŁE, ZASILANIE 12...30VAC/DC.

| | | | | |
|---|---|---|---|---|
| Temperatura | | | | |
| | Temperatura pracy | | | |
| | | min. | °C | -25 |
| | | maks. | °C | +70 |
| | Temperatura składowania | | | |
| | | min. | °C | -40 |
| | | maks. | °C | +85 |

## Certyfikaty i zgodność

| | |
|---|---|
| Zgodność | |
| | CSA C22.2 n° 14 |
| | IEC/EN/BS 60947-1 |
| | IEC/EN/BS 60947-5-1 |
| | UL508 |
| Certyfikaty | |
| | CCC |
| | cULus |
| | EAC |
| | RINA |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding