LPCBL106K11PM6

ZESTAW: PRZYCISK PLASTIKOWY PODŚWIETLANY, SAMOCZYNNY POWRÓT, KRYTY, NIEBIESKI. ADAPTER MONTAŻOWY. ZESTYKI 1NO+1NC, ZACISKI ŚRUBOWE. LAMPKA LED, ŚWIATŁO CIĄGŁE, ZASILANIE 185...265VAC.



Charakterystyka ogólna			
Kolor			Niebieski
Typ pozycji			Przycisk kryty
Stopień ochrony według IEC			IP66, IP67 oraz IP69K
Właściwości elektryczne			
Znamionowe napięcie izolacji Ui IEC/EN		V	690
Prąd roboczy termiczny umowny Ith, IEC ≤ 40°C		A	10
Napięcie zasilania (AC)		V	185…265
Napięcie zasilania (DC)		V	185…265
Przewodność			1mA 5V
Oznaczenie UL/CSA i PN-EN 60947-5-1			A600 Q600
Prąd roboczy AC15			
	12 V	A	6
	24 V	A	6
	48 V	A	6
	120 V	A	6
	240 V	A	3
	400 V	A	1.9
	480 V	A	1.5
	500 V	A	1.4
	600 V	A	1.2
Prąd roboczy DC13			
	12 V	A	3
	24 V	A	3
	48 V	A	1.5
	125 V	A	0.55
	250 V	A	0.27
	440 V	A	0.15
	500 V	A	0.13
	600 V	A	0.1
Rezystancja zestyków		mΩ	≤20
Trwałość			
elektryczna		hours	100000
Właściwości mechaniczne			
Siła zadziałania		kg-lb	<0.5Kg / 1.1lb
Zacisk śrubowy			Śruba
Przekrój przewodu			
IEC			
	maks.	mm²	1 or 2 / 2.5
Adapter do montażu			LPXAU120
Dane techniczne UL			
Stopień ochrony według UL			Typ 1, 2, 3R, 4, 4X, 12, 12K
Warunki otoczenia			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

LPCBL106K11PM6

ZESTAW: PRZYCISK PLASTIKOWY PODŚWIETLANY, SAMOCZYNNY POWRÓT, KRYTY, NIEBIESKI. ADAPTER MONTAŻOWY. ZESTYKI 1NO+1NC, ZACISKI ŚRUBOWE. LAMPKA LED, ŚWIATŁO CIĄGŁE, ZASILANIE 185...265VAC.

Temperatura

Temperatura pracy			
	min.	°C	-25
	maks.	°C	+70
Temperatura składowania			
	min.	°C	-40
	maks.	°C	+85

Certyfikaty i zgodność

Zgodność

- CSA C22.2 n° 14
- IEC/EN/BS 60947-1
- IEC/EN/BS 60947-5-1
- UL508

Certyfikaty

- CCC
- cULus
- EAC
- RINA

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding