# 7GN4056P

ENCLOSED ROTARY CAM SWITCH 7GN SERIES, CHANGEOVER SWITCH WITHOUT 0, 3 POLES 40A IN PLASTIC ENCLOSURE 110X110MM WITH BLACK HANDLE

## General characteristics

| | |
|---|---|
| Switching diagram | 56 - Changeover switch without 0 3 poles |
| N° of elements | 3 |
| Mounting form | P - Plastic enclosure with black handle |

## Contact characteristics

| | | | |
|---|---|---|---|
| Rated insulation voltage Ui | | | |
| | IEC/EN | V | 690 |
| | UL/CSA | V | 600 |
| Rated impulse withstand voltage Uimp | | kV | 6 |
| Conventional free air thermal current Ith | | | |
| | IEC/EN | A | 40 |
| | UL/CSA | A | 50 |
| Rated operational voltage | | V | 480 |
| Rated operational impulse voltage | | kV | 4 |
| Maximum fuse size for short-circuit protection In (gG) | | | |
| | 10kA | A | 40 |
| | 15kA | A | 40 |
| | 25kA | A | 40 |
| | 50kA | A | 40 |
| | 63kA | A | 40 |
| Rated short time current Icw | | | |
| | 1s | kA | 1000 |
| Conductivity | | | 10/5 mA/V |
| Operational current Ie IEC/EN | | | |
| AC1/AC21A | | | |
| | | A | 40 |
| AC15 | | | |
| | 110V | A | 25 |
| | 220/230V | A | 22 |
| | 380/400V | A | 12 |
| | 660/690V | A | 2 |
| Rated operational power in AC | | | |
| Three-phase AC-3 | | | |
| | 220/230V | kW | 8 |
| | 380/440V | kW | 15 |
| | 500/690V | kW | 15 |
| Single-phase AC-3 | | | |
| | 110V | kW | 3 |
| | 220/230V | kW | 6.5 |
| | 380/440V | kW | 8 |
| Three-phase AC23A | | | |
| | 220/230V | kW | 8 |
| | 380/440V | kW | 18.5 |
| | 500/690V | kW | 22 |
| Single-phase AC23A | | | |
| | 110V | kW | 3 |
| | 220/230V | kW | 6 |
| | 380/440V | kW | 11 |
| Rated operational current in DC | | | |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

| | | | | |
|---|---|---|---|---|
| | DC21A | | | |
| | | 48V | A | 40 |
| | | 60V | A | 40 |
| | | 110V | A | 6 |
| | | 220V | A | 0.9 |
| | DC23A (poles in series) | | | |
| | | 24V | A | 40 (1) |
| | | 48V | A | 40 (2) |
| | | 60V | A | 40 (3) |
| | | 110V | A | 20 (3) |
| | | 220V | A | 12 (4) |
| | DC13 | | | |
| | | 24V | A | 40 |
| | | 48V | A | 32 |
| | | 60V | A | 16 |
| | | 110V | A | 3 |
| Power dissipation | | | W | 2.0 |
| **Mechanical features** | | | | |
| Terminals screw | | | | M4 |
| Tightening torque for terminals max | | | Nm | 1.2 |
| Conductor size | | | | |
| | AWG - Rigid cable | | | |
| | | min | AWG | 16 |
| | | Max | AWG | 8 |
| | AWG - Flexible cable | | | |
| | | min | AWG | 16 |
| | | Max | AWG | 10 |
| | Conductor size (IEC) - Flexible cable | | | |
| | | min | mm² | 1.5 |
| | | Max | mm² | 6 |
| | Conductor size (IEC) - Rigid cable | | | |
| | | min | mm² | 1.5 |
| | | Max | mm² | 10 |
| Mechanical life | | | cycles | 5x10⁶ |
| **UL technical data** | | | | |
| Motor power for direct-on-line control | | | | |
| | for three-phase motor | | | |
| | | 120V | HP | 5 |
| | | 240V | HP | 10 |
| | | 480V | HP | 20 |
| | | 600V | HP | 20 |
| | for single-phase motor | | | |
| | | 120V | HP | 2 |
| | | 240V | HP | 5 |
| **Ambient conditions** | | | | |
| Temperature | | | | |
| | Operating temperature | | | |
| | | min | °C | -25 |
| | | max | °C | +55 |
| | Storage temperature | | | |
| | | min | °C | -40 |
| | | max | °C | +70 |
| **Resistance & Protection** | | | | |
| Frontal IP degree | | | | IP65 |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

# 7GN4056P

ENCLOSED ROTARY CAM SWITCH 7GN SERIES, CHANGEOVER SWITCH WITHOUT 0, 3 POLES 40A IN PLASTIC ENCLOSURE 110X110MM WITH BLACK HANDLE


| | |
|---|---|
| Terminals IP degree | IP00 |

## Dimensions

| Series | Enclosure size | Number of elements | | Dimensions | | | | | | | | | | Cable entry | Protection degree |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | L | L1 | A | A1 | C | C1 | D | F | M | N | L | L1 | | |
| 7GN12❶ | 75x75❸ | 1 - 2 | 3 - 4 | 75 | 75 | 50 | 64 | 4.5 | 19 | 14 | 28 | 57.5 | 79.8 | 4xPG13.5 | IP65 |
| 7GN20❶ | | 1 - 2 | 3 - 4 | | | | | | | | | | | | |
| 7GN25❶ | | 1 | 2 - 3 | | | | | | | | | | | | |
| 7GN12❷ | 90x90 | 1 - 3 | 4 - 6 | 90 | 90 | 79 | 63 | 4.5 | 25 | 19 | 30 | 71.3 | 98.3 | 4xPG16 | IP65 |
| 7GN20❷ | | 1 - 3 | 4 - 6 | | | | | | | | | | | | |
| 7GN25❷ | | 1 - 2 | 3 - 4 | | | | | | | | | | | | |
| 7GN32 | | 1 | 2 - 3 | | | | | | | | | | | | |
| 7GN40 | | 1 | 2 - 3 | | | | | | | | | | | | |
| 7GN12 | 110x110 | 1 - 4 | 5 - 8 | 110 | 110 | 98.4 | 83 | 4.5 | 32 | 21 | 39.5 | 85.5 | 119.5 | 4xPG21 | IP65 |
| 7GN20 | | 1 - 4 | 5 - 8 | | | | | | | | | | | | |
| 7GN25 | | 1 - 3 | 4 - 5 | | | | | | | | | | | | |
| 7GN32❶ | | 1 - 2 | 3 - 5 | | | | | | | | | | | | |
| 7GN40❶ | | 1 - 2 | 3 - 5 | | | | | | | | | | | | |
| 7GN63 | | 1 - 2 | 3 - 4 | | | | | | | | | | | | |
| 7GN32❷ | 125x175 | 1 - 2 | 3 - 4 | 125 | 175 | 146 | 112 | 5.5 | 32 | 21 | 68 | 84.3 | 118.3 | 4xPG21 2xPG11 | IP65 |
| 7GN40❷ | | 1 - 2 | 3 - 4 | | | | | | | | | | | | |
| 7GN63❶ | | 1 - 2 | 3 - 4 | | | | | | | | | | | | |
| 7GN125 | | 1 | 2 | | | | | | | | | | | | |
| 7GN32 | 198x248 | – | 1 - 7 | 198 | 248 | 190-210 | 140-180 | 5.5 | 32 | 35 | 104 | – | 166.5 | 6xPG16-21-29 | IP65 |
| 7GN40 | | – | 1 - 7 | | | | | | | | | | | | |
| 7GN63❷ | | – | 1 - 6 | | | | | | | | | | | | |
| 7GN125❶❷ | | – | 1 - 4 | | | | | | | | | | | | |

❶ Standard dimensions for cam switch in plastic enclosure with black handle (P).
❷ DStandard dimensions for cam switch in plastic enclosure with red/yellow handle padlockable in 0 (P25).

## Wiring diagrams




## Certifications and compliance

Compliance

| |
|---|
| IEC/EN/BS 60947-1 |
| IEC/EN/BS 60947-3 |
| IEC/EN/BS 60947-5-1 |

Certificates

EAC

## ETIM classification

| | |
|---|---|
| ETIM 8.0 | EC001029 - Selector switch, complete |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding