8LB6S2B8

SOUND-LIGHT PULSED OR CONTINUOUS MODULE. Ø62MM. BULB INCLUDED, WHITE, 24VAC/DC (80DB)





General characteristics				
Diameter			mm - inch	62 / 2.44
Supply voltage (AC)			V	24
Supply voltage (DC)			V	24
Colour				White
IEC degree of protection				IP54
Sound module consumption (AC)			mA	150
Sound module consumption (DC)			mA	150
Sound intensity			dB	80
Mechanical features				
Tightening torque for terminals max			Nm	0.5
Terminals screw				Screw clamp terminals
Conductor section				
	AWG/Kcmil			
		max		16
	IEC			
		max	mm²	1.5
Weight			g	60
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-20
		max	°C	+50
Dimensions				

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding


8LB6S2B8

SOUND-LIGHT PULSED OR CONTINUOUS MODULE. Ø62MM. BULB INCLUDED, WHITE, 24VAC/DC (80DB)





Wiring diagrams



Certifications and compliance

Compliance

	IEC/EN 60947-1
	IEC/EN 60947-5-1

Certificates

	EAC

ETIM classification

ETIM 8.0	EC000232 - Optical module for signal tower

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding