# BFA00970024

COMPLETA STAR-DELTA STARTER, OPEN FRAME, FOR STARTING TIME UP TO 12 SECONDS AND A MAXIMUM OF 30 OPERATIONS/HOUR, MAX IEC OPERATING CURRENT 16A. COIL VOLTAGE 24VAC 50/60HZ



## Electrical features

| | | |
|---|---|---|
| Maximum operating current (≤440V) | A | 16 |

## Components

| | |
|---|---|
| Contactor standard supplied | BF0910A / BF0901A / BF0910A |
| Thermal relay standard supplied | No |
| Thermal relay to purchase separately | RF38 |
| Auxiliary contact standard supplied | BFX1020 / / BFX1011 |

## Contact characteristics


IEC standard motor powers


| | | |
|---|---|---|
| 230V | kW | 4 |
| 400V | kW | 7.5 |
| 440V | kW | 7.5 |
| 500V | kW | 7.5 |

## Mechanical features

| | | |
|---|---|---|
| Weight | g | 1700 |

## Dimensions





| STARTER TYPE | A | B |
|---|---|---|
| BFA009 70 | 130.5 (5.14") | 109.5 (4.31") |
| BFA012 70 | 130.5 (5.14") | 109.5 (4.31") |
| BFA018 70 | 130.5 (5.14") | 109.5 (4.31") |
| BFA025 70 | 130.5 (5.14") | 109.5 (4.31") |
| BFA026 70 | 135 (5.14") | 119 (4.68") |
| BFA032 70 | 135 (5.14") | 119 (4.68") |
| BFA038 70 | 135 (5.14") | 119 (4.68") |
| BFA050 70 | 173 (6.81") | 142 (5.59") |
| BFA065 70 | 173 (6.81") | 142 (5.59") |
| BFA080 70 | 183 (7.20") | 142 (5.59") |


## Wiring diagrams


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

# BFA00970024

COMPLETA STAR-DELTA STARTER, OPEN FRAME, FOR STARTING TIME UP TO 12 SECONDS AND A MAXIMUM OF 30 OPERATIONS/HOUR, MAX IEC OPERATING CURRENT 16A. COIL VOLTAGE 24VAC 50/60HZ




## Certifications and compliance

Compliance

| | |
|---|---|
| | IEC/EN 60947-1 |
| | IEC/EN 60947-4-9 |

Certificates

/

## ETIM classification

| | |
|---|---|
| ETIM 8.0 | EC001037 - Motor starter/Motor starter combination |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding