GF1067U

ROTARY CAM SWITCH GF SERIES, VOLTMETER SWITCH FOR PHASE-PHASE VOLTAGES 10A, FOR FRONT MOUNTING WITH BLACK HANDLE, FRONT PLATE 30X30MM

General characteristics

Switching diagram			67 - Voltmeter switch for phase-phase voltages
N° of elements			2
Mounting form			U - Front mounting with black handle

Contact characteristics


Rated insulation voltage Ui			
	IEC/EN	V	480
	UL/CSA	V	240
Rated impulse withstand voltage Uimp		kV	4
Conventional free air thermal current Ith			
	IEC/EN	A	10
	UL/CSA	A	10
Rated operational voltage		V	480
Rated operational impulse voltage		kV	4
Maximum fuse size for short-circuit protection In (gG)			
	10kA	A	16
Rated short time current Icw			
	1s	kA	250
Conductivity			10/5 mA/V
Operational current Ie IEC/EN			
AC1/AC21A			
		A	10
AC15			
	110V	A	5
	220/230V	A	3
	380/400V	A	2
Rated operational power in AC			
Three-phase AC-3			
	220/230V	kW	1.5
	380/440V	kW	2.2
Single-phase AC-3			
	110V	kW	0.3
	220/230V	kW	0.55
	380/440V	kW	0.75
Three-phase AC23A			
	220/230V	kW	1.8
	380/440V	kW	3
Single-phase AC23A			
	110V	kW	0.7
	220/230V	kW	0.75
	380/440V	kW	1.1
Rated operational current in DC			
DC21A			
	48V	A	10
	60V	A	7
	110V	A	2
	220V	A	0.7
	440V	A	0.2
DC13			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding


GF1067U


ROTARY CAM SWITCH GF SERIES, VOLTMETER SWITCH FOR PHASE-PHASE VOLTAGES
10A, FOR FRONT MOUNTING WITH BLACK HANDLE, FRONT PLATE 30X30MM

24V	A	3
48V	A	3
60V	A	2
110V	A	1
220V	A	0.3
440V	A	0.1
Power dissipation	W	0.4
Mechanical features		
Terminals screw		2.5M
Tightening torque for terminals max	Nm	0.4
Conductor size		
AWG - Rigid cable		
min	AWG	20
Max	AWG	14
AWG - Flexible cable		
min	AWG	20
Max	AWG	14
Conductor size (IEC) - Flexible cable		
min	mm²	0.5
Max	mm²	1.5
Conductor size (IEC) - Rigid cable		
min	mm²	0.5
Max	mm²	1.5
Mechanical life	cycles	1x10⁶
UL technical data		
Motor power for direct-on-line control		
for three-phase motor		
240V	HP	2
for single-phase motor		
240V	HP	0.75
Ambient conditions		
Temperature		
Operating temperature		
min	°C	-25
max	°C	+55
Storage temperature		
min	°C	-40
max	°C	+70
Resistance & Protection		
Frontal IP degree		IP40
Terminals IP degree		IP20
Dimensions		




GF10





GF20




Drillings for 4 screws fixing (4V version).

Series	Dimensions								L Number of elements											
	□A	C	D	ØD1	ØD2	E	□K	N	1	2	3	4	5	6	7	8	9	10	11	12
GF10	30	24	29	9	3.2	18.5	–	Ø5	40	52	64	76	88	100	112	124	–	–	–	–
GF20	48	39.5	36	12	5	26.5	36	□6	44	57.5	71	84.5	98	111.5	125	138.5	152	165.5	179	192.5

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-3
IEC/EN/BS 60947-5-1
UL60947-4-1

Certificates

cULus
EAC

ETIM classification

ETIM 8.0	EC001029 - Selector switch, complete

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding