GLXM1A230

SPARE MOTOR OPERATOR FOR MOTORISED CHANGEOVER SWITCHES TYPE GLCM… A230



Mechanical features			
Conductor section			
Weight		g	2800
Motor data			
Rated operational voltage		V	208…277VAC
Operating voltage range			166…332VAC
Operating time			
	I-O, O-I	s	0.55…0.89
	I-O-II, II-O-I	s	1.0…1.4
Rated current (In)		A	0.36…0.44
In-rush current		A	0.9…1.1
Switching rate			
	Max continuous Cycles/min		1
	Short time Cycles/min		10
Terminal blocks data			
Conductor section			
	IEC min	mm²	0.2
	IEC max	mm²	2.5
	AWG/kcmil min		24
	AWG/kcmil max		14
Ambient conditions			
Operating temperature			
	min	°C	-25
	max	°C	+55
Storage temperature			
	min	°C	-40
	max	°C	+70
Max altitude		m	3000
Resistance & Protection			
Pollution degree			3
Certifications and compliance			
Compliance			
	IEC/EN/BS 60947-3		
	IEC/EN/BS 6947-6-1		

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding