LPCBL7124K11PM

KIT PLASTIC DOUBLE-TOUCH ACTUATOR, SPRING RETURN, WHITE INDICATOR, 2 FLUSH PUSHBUTTONS, WHITE BLACK/I 0 WITH MOUNTING ADAPTER AND 2 CONTACT ELEMENTS, 1NO+1NC. SCREW TERMINATION. LED INTEGRATED LAMP-HOLDER, STEADY LIGHT, 185...265VAC



General characteristics			
Colour			White/Black
Type of positions			Double-touch with two flush pushbuttons
IEC degree of protection			IP66, IP67 and IP69K
Electrical characteristics			
Rated insulation voltage Ui IEC/EN		V	690
IEC Conventional free air thermal current Ith ≤ 40°C		A	10
Supply voltage (AC)		V	185…265
Supply voltage (DC)		V	185…265
Conductivity			1mA 5V
UL/CSA and IEC/EN 60947-5-1 designation			A600 Q600
Operating current AC15			
	12V	A	6
	24V	A	6
	48V	A	6
	120V	A	6
	240V	A	3
	400V	A	1.9
	480V	A	1.5
	500V	A	1.4
	600V	A	1.2
Operating current DC13			
	12V	A	3
	24V	A	3
	48V	A	1.5
	125V	A	0.55
	250V	A	0.27
	440V	A	0.15
	500V	A	0.13
	600V	A	0.1
Contact resistance		mΩ	≤20
Operations			
Electrical life		hours	100000
Mechanical features			
Operating force		kg-lb	<0.5Kg / 1.1lb
Mechanical life		cycles	1000000
Terminals screw			Screw
Conductor section			
IEC			
	max	mm²	1 or 2 / 2.5
Mounting adapter			LPXAU120
UL technical data			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

LPCBL7124K11PM

KIT PLASTIC DOUBLE-TOUCH ACTUATOR, SPRING RETURN, WHITE INDICATOR, 2 FLUSH PUSHBUTTONS, WHITE BLACK/I 0 WITH MOUNTING ADAPTER AND 2 CONTACT ELEMENTS, 1NO+1NC. SCREW TERMINATION. LED INTEGRATED LAMP-HOLDER, STEADY LIGHT, 185...265VAC

UL degree of protection	Type1, 2, 3R, 4, 4X, 12, 12K

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+70

Storage temperature

min	°C	-40
max	°C	+85

Certifications and compliance

Compliance

- CSA C22.2 n° 14
- IEC/EN/BS 60947-1
- IEC/EN/BS 60947-5-1
- UL508

Certificates

- CCC
- cULus
- EAC
- RINA

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding