**Data sheet**

# 020PFGR

Pulsante a fungo Ø 38, grigio





## Features

| | |
|---|---|
| Range | 020 Comando e Segnalazione SM2 Ø 22 |
| Product | Pulsanti a fungo non luminosi Ø 22 |
| Type | Fungo Ø 38 |
| Item code | 020PFGR |
| Description | Pulsante a fungo Ø 38, grigio |
| Colour | Grigio |
| Weight - gr | 24,000 |
| Custom tariff no. | 85365080 |
| GTIN | 8052878005467 |

## Technical data

| | |
|---|---|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2, CEI EN 61373 |
| Operating temperatures | -40° ÷ +70°C |
| Protection degree | IP66 - IP69K (IEC-EN60529 - DIN40050) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 3.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 8 blocks (4+4) |
| Material | PA Polyamide |
| Button/mushroom material (illuminated type) | PC Polycarbonate |
| Locking ring material | ZAMAK zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Actuation type | Spring return |
| Overvoltage category | Class II (IEC-EN61140) |
| Warranty period | 18 months |

## Technical drawings

