**Data sheet**

# 020STAMTBLWS

Selettore a manopola, blu, 3 posizioni, Cam T, ritorno a molla da sx, metallo






## Features


| | |
|---|---|
| Range | 020 Comando e Segnalazione SM2 Ø 22 |
| Product | Selettori a manopola non luminosi Ø 22 - ghiera in metallo |
| Type | 3 posizioni |
| Item code | 020STAMTBLWS |
| Description | Selettore a manopola, blu, 3 posizioni, Cam T, ritorno a molla da sx, metallo |
| Colour | Blu |
| Weight - gr | 38,000 |
| Custom tariff no. | 85365080 |
| GTIN | 8052878025786 |

## Technical data

| | |
|---|---|
| Approvals | CE |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Compliance with standards | UNI CEI EN 45545-2 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK03 (IEC-EN62262) |
| Mechanical durability | 1.000.000 Operations |
| Shock resistance | 30g duration=18ms (EN-IEC 60068-2-27) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Vibration resistance | 5g f= 2...500Hz (EN-IEC 60068-2-6) |
| Contact blocks configuration | Max no. 4 blocks (2+2) |
| Knob or lever material | PC Polycarbonate |
| External bezel material | Chromed zinc alloy |
| Locking ring material | ZAMAK zinc alloy |
| Fixing diameter | 22.5mm - Thickness 1÷6mm |
| Tightening torque | 2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in) |
| Overvoltage category | Class II (IEC-EN61140) |
| Warranty period | 18 months |


## Technical drawings





**CAM T**






020E01
020E10
020G

