
SIEMENS

Foglio dati 3RW5907-0PY04

scheda 480 V per 3RW50, grandezza costruttiva S12



denominazione del prodotto	Scheda
esecuzione del prodotto	480 V
designazione del tipo di prodotto	3RW59
n. di articolo del produttore del softstarter	
•	3RW507.-..B.4
Dati tecnici generali	
Direttiva RoHS (data)	09/23/2019
SVHC substance name	Lead CAS-No. 7439-92-1 Lead monoxide (lead oxide) CAS-No. 1317-36-8 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol CAS-No. 79-94-7 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1
Peso netto per UQ	0,4 kg
Condizioni ambientali	
temperatura ambiente durante l'immagazzinaggio	-40 ... +80 °C

Approvazioni Certificati

Environment	General Product Approval				EMV
Environmental Confirmations					

For use in hazardous locations	Test Certificates	Maritime application			
Miscellaneous	Type Test Certificates/Test Report	ABS	DNV	LRS	PRS

other		
产品合格 QC PASS	Confirmation	Confirmation

Con riserva di modifiche
© Copyright Siemens

Ulteriori informazioni

Informazioni sull'imballaggio
https://support.industry.siemens.com/cs/ww/it/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Cataloghi, Opuscoli,…)
https://www.siemens.com/ic10
Industry Mall (sistema di ordinazione Online)
https://mall.industry.siemens.com/mall/it/it/Catalog/product?mlfb=3RW5907-0PY04
Service&Support (Manuali, Certificati, Caratteristiche, FAQ, …)
https://support.industry.siemens.com/cs/ww/it/ps/3RW5907-0PY04
Banca dati immagini (foto prodotto, disegni dimensionali 2D, modelli 3D, schemi delle connessioni, macro EPLAN…)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5907-0PY04&lang=en
Generatore CAx online
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5907-0PY04
Curve caratteristiche
https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod__no>
Caratteristica: Comportamento di sgancio, I²t, Corrente di interruzione limitata
https://support.industry.siemens.com/cs/ww/en/ps/3RW5907-0PY04/char
Curve caratteristiche: Altitudine di installazione
https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&objkey=G_NSB0_XX_01704&showdetail=true&view=Search
Simulation Tool for Soft Starters (STS)
https://support.industry.siemens.com/cs/ww/en/view/101494917

Ultima modifica: 17/04/2025

© Copyright Siemens

Con riserva di modifiche
© Copyright Siemens