K

2013






- Apparecchio di illuminazione che impiega LED ad alto rendimento.
- Installazione a soffitto.
- Luce monocromatica.
- Composto da cornice, corpo, lente, molle di fissaggio.
- Cornice in stampo di ABS, verniciato.
- Corpo dissipatore in pressofusione di alluminio (K 35) o in estrusione di alluminio (K 55).
- Lente in PMMA in 2 versioni di fasci diversi.
- Molle di fissaggio in nylon (K 35) o in acciaio armonico (K 55).
- Collegamento elettrico ad alimentatore tramite cavo FROR.
- LED monocromatici bianchi in 2 temperature di colore:
  Caldo = 3000K
  Neutro = 4000K
- Grado di protezione IP20.
- Classe elettrica III.
- Caratteristiche tecniche degli apparecchi conformi alla EN60598-1.
- Il montaggio va eseguito da personale specializzato.
- Seguire scrupolosamente le istruzioni.

- Light fixture with high-performance LED light sources.
- Ceiling installation.
- Composed by: frame, body, lens, fixing springs.
- Frame in injection mould of ABS, painted.
- Heat sink body in injection mould of aluminium (K 35) or in extruded aluminium (K 55).
- Lens in PMMA with 2 different versions of beam.
- Fixing springs in nylon (K 35) or in harmonic steel (K 55).
- Electrical connection to the driver by means of a FROR cable.
- White monochromatic LEDs available in 2 colour temperatures:
  Warm = 3000K
  Neutral = 4000K
- IP Rating IP20.
- Insulation class III.
- Technical features of light fixtures in compliance with EN60598-1.
- Installation must be carried out by specialized personnel.
- Carefully follow the instructions.







ø 50 ±2mm

**K 55 Round Adjustable**

grigio
nero
bianco
Cornice in ABS
Molle fissaggio
in acciaio armonico
Alimentatore remoto
fornito a parte
Orientazione: +25°


*grey*
*black*
*white*
*Frame in ABS*
*Fixing springs in harmonic steel*
*Remote driver supplied separately*
*Tilting angle:* +25°

| | Source | Power | CCT | Beam | Efficacy | |
|---|---|---|---|---|---|---|
| **NL4203318K002** | 1 LED | 7W | 3000K | 18° | 48 lm/W | |
| **NL4203318W002** | 1 LED | 7W | 4000K | 18° | 51 lm/W | |
| **NL4203318K004** | 1 LED | 7W | 3000K | 18° | 48 lm/W | ● |
| **NL4203318W004** | 1 LED | 7W | 4000K | 18° | 51 lm/W | ● |
| **NL4203318K006** | 1 LED | 7W | 3000K | 18° | 48 lm/W | ○ |
| **NL4203318W006** | 1 LED | 7W | 4000K | 18° | 51 lm/W | ○ |




K 55 - 7W - 3000K - 18°

| | Source | Power | CCT | Beam | Efficacy | |
|---|---|---|---|---|---|---|
| **NL4203334K002** | 1 LED | 7W | 3000K | 34° | 48 lm/W | |
| **NL4203334W002** | 1 LED | 7W | 4000K | 34° | 51 lm/W | |
| **NL4203334K004** | 1 LED | 7W | 3000K | 34° | 48 lm/W | ● |
| **NL4203334W004** | 1 LED | 7W | 4000K | 34° | 51 lm/W | ● |
| **NL4203334K006** | 1 LED | 7W | 3000K | 34° | 48 lm/W | ○ |
| **NL4203334W006** | 1 LED | 7W | 4000K | 34° | 51 lm/W | ○ |






K 55 - 7W - 3000K - 34°

| CRI 80 min. | 3000K 340 lm | 4000K 361 lm | IP20 | F | III | Kg 0,20 | CE |
|---|---|---|---|---|---|---|---|

alimentazione elettronica 500mA
*500mA electronic ballast*

| | | | | |
|---|---|---|---|---|
| **NL10941** | Alimentatore *Driver* | 8W | 500mA | 1 max |
| **NL19034** | Alimentatore *Driver* | 20W | 500mA | 2 max |







□ 50 ±2mm

**K 55 Square Adjustable**

grigio
nero
bianco
Cornice in ABS
Molle fissaggio
in acciaio armonico
Alimentatore remoto
fornito a parte
Orientazione: +25°


*grey*
*black*
*white*
*Frame in ABS*
*Fixing springs in harmonic steel*
*Remote driver supplied separately*
*Tilting angle:* +25°

| | Source | Power | CCT | Beam | Efficacy | |
|---|---|---|---|---|---|---|
| **NL4203218K002** | 1 LED | 7W | 3000K | 18° | 48 lm/W | |
| **NL4203218W002** | 1 LED | 7W | 4000K | 18° | 51 lm/W | |
| **NL4203218K004** | 1 LED | 7W | 3000K | 18° | 48 lm/W | ● |
| **NL4203218W004** | 1 LED | 7W | 4000K | 18° | 51 lm/W | ● |
| **NL4203218K006** | 1 LED | 7W | 3000K | 18° | 48 lm/W | ○ |
| **NL4203218W006** | 1 LED | 7W | 4000K | 18° | 51 lm/W | ○ |




K 55 - 7W - 3000K - 18°

| | Source | Power | CCT | Beam | Efficacy | |
|---|---|---|---|---|---|---|
| **NL4203234K002** | 1 LED | 7W | 3000K | 34° | 48 lm/W | |
| **NL4203234W002** | 1 LED | 7W | 4000K | 34° | 51 lm/W | |
| **NL4203234K004** | 1 LED | 7W | 3000K | 34° | 48 lm/W | ● |
| **NL4203234W004** | 1 LED | 7W | 4000K | 34° | 51 lm/W | ● |
| **NL4203234K006** | 1 LED | 7W | 3000K | 34° | 48 lm/W | ○ |
| **NL4203234W006** | 1 LED | 7W | 4000K | 34° | 51 lm/W | ○ |




K 55 - 7W - 3000K - 34°

| CRI 80 min. | 3000K 340 lm | 4000K 361 lm | IP20 | F | III | Kg 0,20 | CE |
|---|---|---|---|---|---|---|---|

alimentazione elettronica 500mA
*500mA electronic ballast*

| | | | | |
|---|---|---|---|---|
| **NL10941** | Alimentatore *Driver* | 8W | 500mA | 1 max |
| **NL19034** | Alimentatore *Driver* | 20W | 500mA | 2 max |