CDVI
Security to Access

Datasheet

SEL2641R433-NN - 1-relay mini receiver

Product Description

The SEL2641R433-NN is a small, economical, single-channel receiver for standard applications.

The receiver is part of a complete range of radio control and switching products to provide wire-free control of gates, barriers, doors and lights.

The standard read range is up to 200 metres. The output relay can be set for PULSE or TIMED mode. The default pulse is 1 second whilst the timed mode can be set from 1 to 30 seconds.

The receiver has a memory capacity for up to 85 transmitter buttons and has a 12/24 Vac/dc power supply.



Key Features

- Compact miniature receiver
- 1 normally open output relay
- Timed and pulse relay operation modes
- Memory for up to 85 transmitter buttons
- Up to 200m read range
- Ideal for wireless control of automatic doors, gates, lights
- Compatible with all CDVI 433.92 MHz transmitters

CE Certification

DEEE

RoHS Certification

IP2X

-20°C to 70°C

All the information contained within this document (pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. Published: 27 February 2026. CDVI_SEL2641R433NN_DS_05_EN_A4_C

CDVI
Address Line 1
Address Line 2

Email
Phone
Website

10 YEAR WARRANTY